



JUNCTION BOX

Abox-i 350-35²/sw



Abox-i 350-35²/sw

Junction box

CUSTOMIZABLE

250 x 250 x 115 mm
Article number: 49143501

Junction box - Industrial Quality - acc. DIN EN 60670 (VDE 0606), U_i=690V, weathering-proof, shock-proof, halogen-free, with sealing kit, for suitable cable in-feeds see accessories

black, with high-set screw terminals, 5-poles - 35 mm² (4 x 16² / 4 x 25² / 4 x 35²)



Technical data

Measures

Width:	250 mm
Length:	250 mm
Height:	115 mm

Material

Base:	polycarbonate, glass fiber-reinforced
Cover:	polycarbonate, glass fiber-reinforced

Other attributes

Entries:	14
Rated cross section:	35 mm ²
Tackable:	No
Rated insulation voltage AC:	690 V

Accessory

Abox 250/350 KLS-25²/35²

HandyQuick SQ 52

HandyQuick SQ 32

HandyClip VC 21

HandyClip VC 20

HandyGrip VG 21 w

HandyGrip VG 20 w

HandyGrip VG 21

HandyGrip VG 20

KVR M50-MGM

KVR M40-MGM

KVR M32-MGM

KVR M25-MGM

KVR M20-GDB/MGM

KVR M20-MGM

VST M40-or

VST M32-or



JUNCTION BOX

Abox-i 350-35²/sw

Explosion safety:	none
Fire protection:	none
sealable:	Yes
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP65 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	Yes
Equipment:	Terminal
Color:	black

VST M25-or
VST M20-or
AST M40-or
AST M32-or
AST M25-or
AST M20-or
DMS M32
DMS M25
KVR M50
KVR M40
KVR M32
KVR M25
KVR M20-GDB

Environmental attributes

Ambient temperature (24 h):	60 °C
Ambient temperature (max.):	80 °C
Ambient temperature (min.):	-35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%