



JUNCTION BOX

**WK 060-6<sup>2</sup>**



**WK 060-6<sup>2</sup>**

**Junction box**

100 x 100 x 50 mm

Article number: 40640601

Junction box acc. DIN EN 60670 (VDE 0606), Ui=690V, Duroplastic, halogen-free, with IP54 attachment bushes, with blanking plug M25, seal range 9 - 18.5 mm

grey, with screw terminal 5-poles - 6 mm<sup>2</sup>, (5 x 4<sup>2</sup> / 4 x 6<sup>2</sup>)



**Technical data**

**Measures**

Width:	100 mm
Length:	100 mm
Height:	50 mm

**Material**

Base:	Duroplastic
Cover:	Duroplastic
Sealing:	thermoplastic elastomer
Cover screw:	Steel

**Other attributes**

Entries:	6
Rated cross section:	6 mm <sup>2</sup>
Tackable:	No
Rated insulation voltage AC:	690 V

**Accessory**

- KVR M25-MGM
- VST M25-or
- AST M25-or
- DMS M25
- AST M25
- WK 060 KLS-6<sup>2</sup>
- KVR M25
- GMU PA M25
- ADR M25
- WST M25
- WNI M25
- VST M25
- VSS PA M25
- SNI M25
- KS M25
- RST M25
- WST M25/sw



JUNCTION BOX

**WK 060-6<sup>2</sup>**

Explosion safety:	none
Fire protection:	none
sealable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP54 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	No
Equipment:	Terminal
Color:	grey

WNI M25/sw

DMS M25/sw

KVR M25-MGM/sw

MPS-KRI

KVR M25-MGM

VST M25-or

AST M25-or

DMS M25

AST M25

WK 060 KLS-6<sup>2</sup>

KVR M25

GMU PA M25

ADR M25

**Environmental attributes**

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%