



JUNCTION BOX

WK 100-10²



WK 100-10²

Junction box

115 x 115 x 66 mm

Article number: 41040601

Junction box acc. DIN EN 60670 (VDE 0606), U_i=690V, Duroplastic, halogen-free, with IP54 attachment bushes, with blanking plug M32, seal range 13 - 23 mm, with sealing kit

grey, with screw terminal 5-poles - 10 mm², (5 x 4² / 4 x 6² / 3 x 10²)



Technical data

Measures

Width:	115 mm
Length:	115 mm
Height:	66 mm

Material

Base:	Duroplastic
Cover:	Duroplastic
Sealing:	thermoplastic elastomer
Cover screw:	Steel

Other attributes

Entries:	6
Rated cross section:	10 mm ²
Tackable:	No
Rated insulation voltage AC:	690 V

Accessory

KVR M32-MGM

VST M32-or

AST M32-or

DMS M32

AST M32

WK 100 KLS-10²

KVR M32

GMU PA M32

ADR M32

WST M32

VST M32

VSS PA M32

SNI M32

KS M32

KST M32

WNI M32

RST M32



JUNCTION BOX

WK 100-10²

Explosion safety:	none
Fire protection:	none
sealable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP54 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	No
Equipment:	Terminal
Color:	grey

DMS M32/sw
KVR M32-MGM/sw
DMS M32/4
MPS-KRI
KVR M32-MGM
VST M32-or
AST M32-or
DMS M32
AST M32
WK 100 KLS-10 ²
KVR M32
GMU PA M32
ADR M32

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%