



JUNCTION BOX

Abox 025 AB-2,5²/w



Abox 025 AB-2,5²/w

Junction box

CUSTOMIZABLE

80 x 80 x 52 mm
Article number: 80310701

Junction box acc. DIN EN 60670 (VDE 0606), Ui=690V, with self-sealing, soft inlet membranes, M20, seal range 2 - 16 mm, with external fixing lugs

white, with screw terminal, 5-poles - 2.5 mm² (4 x 1.5² / 4 x 2.5²)



Technical data

Measures

Width:	80 mm
Length:	80 mm
Height:	52 mm

Material

Base:	polystrole, membrane out of TPE
Cover:	Polystyrene

Other attributes

Ingress protection:	IP65 - acc. EN 60529 / DIN VDE 0470-1
Entries:	8
Rated cross section:	2,5 mm ²
Rated insulation voltage AC:	690 V

Accessory

- HandyQuick SQ 52
- HandyQuick SQ 32
- HandyClip VC 21
- HandyClip VC 20
- HandyGrip VG 21 w
- HandyGrip VG 20 w
- HandyGrip VG 21
- HandyGrip VG 20
- KVR M20-GDB/MGM
- KVR M20-MGM
- VST M20-or
- AST M20-or
- DMS M20
- RST M20
- HandyQuick SQ51
- HandyQuick SQ81
- Abox 025/040 KLS-2,5²/4²



JUNCTION BOX

Abox 025 AB-2,5²/w

sealable:	Yes
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Weatherproof:	No
Equiptment:	Terminal
Color:	white

HandyQuick SQ 31
WST M20/sw
WNI M20/sw
KVR M20-MGM/sw
KVR M20-GDB/MGM/sw
MPS-KRI
AST M20
KVR M20-GDB
KVR M20
GMU PA M20
ADR M20
WST M20
WNI M20

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%