



Dimension drawing DFL D

Basic circuit diagram DFL D

DFL D: Surge arrester for use in all kinds of installation systems on terminal equipment level; allows for series connection; with test function

- Two-pole surge protection with control device and disconnecter
- Maximum safety due to confusion-proof Y protection circuit
- Acoustic fault indicator
- Compact design
- For use in flush-mounted systems, cable ducts and wiring sockets

DFL D 255	
SPD according to EN 61643-11	Type 3
SPD according to IEC 61643-1	Class III
Nominal a.c. voltage [U <sub>Nl</sub> ]	230 V
Max. continuous operating a.c. voltage [U <sub>Ci</sub> ]	255 V
Nominal load current a.c. [I <sub>l1</sub> ]	16 A
Nominal discharge current (8/20 μs) [I <sub>n1</sub> ]	3 kA
Total discharge current (8/20 μs) [L+N-PE] [I <sub>total</sub> ]	5 kA
Combined impulse [U <sub>OCi</sub> ]	6 kV
Combined impulse [L+N-PE] [U <sub>OC total</sub> ]	10 kV
Voltage protection level [L-N] [U <sub>p1</sub> ]	≤ 1.25 kV
Voltage protection level [L/N-PE] [U <sub>p1</sub> ]	≤ 1.5 kV
Response time [L-N] [t <sub>A1</sub> ]	≤ 25 ns
Response time [L/N-PE] [t <sub>A1</sub> ]	≤ 100 ns
Max. mains-side overcurrent protection	16 A gL/gG or B 16 A
Short circuit withstand capability for mains-side overcurrent protection with 16 A gL/gG	6 kA <sub>rms</sub>
Temporary overvoltage (TOV) [L-N] [U <sub>T1</sub> ]	335 V / 5 sec.
Temporary overvoltage (TOV) [L/N-PE] (I) [U <sub>T1</sub> ]	400 V / 5 sec.
Temporary overvoltage (TOV) [L/N-PE] (II) [U <sub>T1</sub> ]	1200 V + U <sub>0</sub> / 20
Indication of disconnecter	acoustic signal on
Operating temperature range [T <sub>U1</sub> ]	-25°C...+40°C
Terminal wires	2.5 mm <sup>2</sup> , length: 120 mm
Enclosure material	red thermoplastic, UL 94 V-2
Degree of protection of installed device	IP 20
Dimension	36 x 62 x 19 mm
<b>Ordering information</b>	
Type	DFL D 255
Part No.	924 395
Packing unit	1pcs.

We reserve the right to modify design, technology, dimensions, weights and materials according to technical progress. Illustrations are non-binding. Pictures may differ from the modules described.