

## POWERCOB DIRECT

## DOWNLIGHTS



IPAS PowerCOB Direct LED Downlight for hhv 140 mm hulluttak eller 170 mm hulluttak, 20W eller 30W Sharp COB erstatter kompaktlysrør og metallhalogen downlight. IP20. Komplet med LED Driver.

ART. NR.	EL.NR.	TEKST	FARGE	ANT/ESKE
242024	<b>32 210 50</b>	Power COB Direct 20W 1235 lm	Hvit/krom	16 stk
243004	<b>32 210 51</b>	Power COB Direct 30W 1850 lm	Hvit/krom	12 stk

	PowerCOB 20W	PowerCOB 30W
Diameter:	160 mm	190 mm
Hulltak:	Ø 140 mm	Ø 170 mm
Innf. høyde:	140 mm	130 mm
Spredningsvinkel:	60 grader	60 grader
Effekt:	20W	30W
Systemeffekt:	21W	31W
LED:	Sharp COB	Sharp COB
Lysytelse:	1235 lm	1850 lm
Levetid (L70):	50 000 t	50 000 t
Lysfarge:	3000K varmhvit	3000K varmhvit
Ra:	>85	>85
LED Driver:	500mA DIM	700mA DIM
Spenning:	100-240V	100-240V
Effektfaktor:	>0,95	>0,95



**SHARP**

**ipas**<sup>TM</sup>