

Tynnvegget krympeslange uten lim



Type B2 3:1 og 2:1

Sort
Gul-Grønn



For elektrisk isolering og fargekoding

Krympeslange type Sumitube B2 (3x)

Materiale fleksibel Polyolefin

Flammehemmende

Temperaturområde -55 - +135°C

Gjennomslagfasthet 37kV pr.mm

MIL-DTL-23053/5 Class1, UL 224 125°C 600V VW-1

VG95343 Teil 5 Typ A (=B20, B20(3x)) , DEF STD 59-97 (=B20, B20(3x))



Sort 3:1 og 2:1

Gul-Grønn 3:1 og 2:1

Dim. mmØ	Veggt mm	Pakn rull à m	El.nr	Dim. mmØ	Veggt mm	Pakn rull à m	El.nr
1,5 - 0,5	0,5	50	1833870	1,5 - 0,5	0,5	30	1833019
3 - 1	0,6	50	1833871	3 - 1	0,6	30	1833880
6 - 2	0,7	30	1833872	6 - 2	0,7	30	1833881
9 - 3	0,8	30	1833873	9 - 3	0,8	30	1833882
12 - 4	0,85	30	1833874	12 - 4	0,85	30	1833883
18 - 6	1,00	30	1833875	18 - 6	1,00	30	1833884
24 - 8	1,2	30	1833876	24 - 8	1,2	30	1833885
40 - 13	1,25	30	1833877	40 - 13	1,25	30	1833886
50,8-25,4	1,52	30	1833839	50,8-25,4	1,52	30	1833022
72,6 - 36,3	1,52	30	1833840				
101,6 - 50,8	1,52	15	1833841				