

ISOLATOR 100A SINGLE POLE, RED HANDLE



Similar to image

**Technical data:**

<b>Mounting depth</b>	mm	70
<b>Operating voltage / rated value</b>	V	250
<b>Operating current / rated value</b>	A	100
<b>Type of voltage</b>		AC
<b>Number of poles</b>		1
<b>Breaking capacity current / rated value</b>	kA	0.3
<b>Resistance against short-circuit current</b>	kA	10
<b>Design of the switching function</b>		Switch disconnecter
<b>Number of width units</b>		1
<b>Number of NC contacts</b>		0
<b>Number of NO contacts</b>		1
<b>Number of change-over switches</b>		0
<b>Product component / Signal lamp</b>		No
<b>Product function / positive opening (acc. to DIN VDE 0113)</b>		No

**Certificates/approvals:**

General Product  
Approval

Declaration of Conformity



**Further information:**

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5TL1191-1>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/5TL1191-1/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TL1191-1](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TL1191-1)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

last change:

Sep 1, 2014