

ISOLATOR 80A TRIPLE POLE+NEUTRAL



Similar to image

Technical data:

<b>Mounting depth</b>	mm	70
<b>Operating voltage / rated value</b>	V	440
<b>Operating current / rated value</b>	A	80
<b>Type of voltage</b>		AC
<b>Number of poles</b>		3
• note		3P+N
<b>Breaking capacity current / rated value</b>	kA	0.24
<b>Resistance against short-circuit current</b>	kA	10
<b>Design of the switching function</b>		Switch disconnecter
<b>Number of width units</b>		4
<b>Number of NC contacts</b>		0
<b>Number of NO contacts</b>		3
<b>Number of change-over switches</b>		0
<b>Product component / Signal lamp</b>		No
<b>Product function / positive opening (acc. to DIN VDE 0113)</b>		No

Certificates/approvals:

General Product  
Approval

Declaration of Conformity



#### Further information:

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5TL1680-0>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5TL1680-0/all>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TL1680-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TL1680-0)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

##### Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

last change:

Sep 1, 2014