



product description: intended for installation to the distribution of low voltage
 designed for installation in the corner between the floor and wall of the room as well as between two walls, or wall and ceiling edge with softened spray application for better adhesion to the surface
 length adjusted to standard room height

material: PVC - Pb-free
 self-snuffing: yes, within 30 s
 temperature resistance: -5 - +60 °C
 flaming loop test: 850 °C
 impact strength: 0,5 J
 protection types: IP40
 fire class for underlying material: A1-F
 inside area: 560 mm²
 distance base perforation: 200 ±20 mm
 length tolerance: ±10 mm
 weight: 0,34 kg/m
 meets the requirements: EN 50085-1 ed.2:06, EN 50085-2-1:07
 storage: ČSN 64 0090



usage of inner trunking cross-section (60%):	orientation cable diameter (mm)	6	7	8	8,5	9	9,5	10	11	12	13	14	15	16
	number of inserted cables	11	8	6	5	5	4	4	3	2	2	2	1	1

chemical resistance: YES: amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate
 NO: aceton, benzen, chlorinated hydrocarbons, tetrachlorocarbon

item number	length	color	package	package - description	note
LR 30_HB	2,6 m	white RAL 9003	26 m	carton	-
8855_HB		white RAL 9003	5 / 400 pcs	foil / carton	inner corner
8855/3_HB		white RAL 9003	5 / 370 pcs	foil / carton	inner corner - access from three sides
8856_HB		white RAL 9003	10 / 280 pcs	foil / carton	outer corner