





SBILL-800 Lug-to-Lug Power Terminal – SBLL-800 (561136)



- Tinned copper block allows for copper or aluminum conductor connections
- Accessible studs allow for easy connection of sections of ERIFLEX FLEXIBAR or other conductors
- Design allows for visual inspection of conductor and confirmation of connection
- Adjustable transparent cover
- Gangable for building multi-pole power blocks
- Easily clips onto DIN rail or mounts to panel with screws
- SBLEC Power Terminals Fixing Accessory required for direct panel mount
- Halogen free
- RoHS compliant



| | |
|--|----------------------------------|
| Part Number | SBLL-800 |
| Article Number | 561136 |
| Material | Copper Thermoplastic |
| Finish | Tinned |
| Max Current Rating, IEC | 1,250 A |
| Max Current Rating, UL/CSA | 800 A |
| Short Term Withstand Current [I _{cw}] 1s | 57.6 kA |
| Peak Short Circuit Current [I _{pk}] | 75 kA |
| Short Circuit Current Rating [SCCR] | 100 kA |
| Max Working Voltage, IEC (U _i) | 1,000 VAC 1,500 VDC |
| Max Working Voltage, UL (V _{in}) | 1,000 V |
| Number of Stud Connections | 4 |
| Stud Connection Conductor Width | (2) 20 – 40 mm (1) 50 – 80 mm |
| Stud Connection Compact Stranded Wire Size | (2) 25 – 300 mm ² |
| Stud Connection Wire Size | (2) #4 – 500 kcmil |
| Depth [D] | 75 mm |
| Height [H] | 205.7 mm |
| Width [W] | 115 mm |

| | |
|-----------------------------|---|
| Part Number | SBL-800 |
| A | 108 mm |
| Unit Weight | 0.7 kg |
| Certification Details | UL® 1059 |
| Flammability Rating | UL® 94V-1 |
| Complies With | IEC® 60947-7-1 |
| Certifications | cURus EAC 0234267 (Russian Federation) RoHS |
| Standard Packaging Quantity | 1 pc |
| UPC | 78285663096 |
| EAN-13 | 8711893054026 |

| Design Guideline for Distribution Blocks, Power Blocks and Power Terminals | | | | | | | | | | |
|---|-----|-----|-----|------|------|------|------|------|------|------|
| Derating according to Ambient* Temperature (°C) to maintain working temperature of 85°C | | | | | | | | | | |
| Ambient Temperature (°C) | 30° | 35° | 40° | 45° | 50° | 55° | 60° | 65° | 70° | 75° |
| Derating Coefficient (d) | 1 | 1 | 1 | 0.94 | 0.88 | 0.82 | 0.75 | 0.67 | 0.58 | 0.47 |
| *environment around the terminal blocks inside the enclosure | | | | | | | | | | |

Power terminal connections are interchangeable and can be used as line side or load side connections.

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.