onnline

Product Information

Name:

Surface-type wall rocker switch for fixed installation

Technical Data: 16AX 250VAC

Frequency: 50Hz Colour: White

Main material: PC (Halogen free)

IP-Class: IP20

Max. Ambient temp.: 45°C

Fire hazard test: 650°C/850°C (IEC60695-2-11) The product complies with the standard(s):

EN60669-1

The product is in conformity with the provisions of the following European

directive(s):

LVD, RoHS, REACH, WEEE **Certificate(s):** CE, Semko

Quality management system according to:

ISO 9001:

Environmental management system:

ISO 1400°

Occupational Health and Safety Management System:

ISO 45001

Technical info:

Wiring diagram printed on the rear side.

Thermoplastic in the rocker and cover plate.

Screw terminals.

Flush wiring.

Screw distance cc 38 mm -cover plate cc 73 mm.

Space enough for cables up to 2.5 mm under the cover plate.

Base bottom plate acts at same time as a positioning guide by the door frame under installation.

Maximum torque for terminal screws: 1.2Nm.




Type

	•
U221	1 pole / 2-way, pattern No. 1/6
U224	1 pole and 2-way , pattern No. 5

Description/Remark

Drawing:

E-No.



Onninen AS Høgslundveien, Berger industriområde 49 Postboks 117 2020 Skedsmokorset



U221



U224

Kontaktmail:onninenpost@onninen.com Telefon: 22 39 60 00



Wiring diagram:

