

Product Information

Name:

Flush-type wall rocker switch for fixed installation

Technical Data: 16A 250VAC

Frequency: 50Hz Colour: White

Main material: PC (Halogen free)

IP-Class: IP20

Max. Ambient temp.: 45°C

Fire hazard test: 650°C/850°C (IEC60695-2-11) The product complies with the standard(s):

EN60669-1

The product is in conformity with the

provisions of the following European directive(s):

LVD, RoHS, REACH, WEEE **Certificate(s):** CE, Semko

Quality management system according to:

ISO 9001

Environmental management system:

ISO 14001

Occupational Health and Safety Management System:

ISO 45001

Technical info:

Can also be surface mounted switch by use of a surface mounting frame 20 mm high.

Wiring diagram printed on the rear side.

Thermoplastic in the rocker and cover plate.

Flush wiring. Screw terminal.

Fit into wall boxes, screw distance cc 60 mm -cover plate cc 84 mm.


With standard 55x55 mm central plate, can fit into our standard combination plate (code named "S").

Maximum torque for terminal screws: 1.2Nm.


Type Designation:

E-No.	Туре	Description/Remark
	U202	2-pole, pattern No. 2

Drawing:



Wiring diagram:



Kontaktmail:onninenpost@onninen.com Telefon: 22 39 60 00