


# onnl<sup>ine</sup>

ONNLINE CEE PLUGG 4P 63A, 230V 9H IP67  
Elnr. 1512948



|                        |          |
|------------------------|----------|
| country of origin      | AT       |
| customs number         | 85366990 |
| net weight             | 0.617 kg |
| packaging quantity     | 2        |
| minimum order quantity | 2        |

|                                 |                           |
|---------------------------------|---------------------------|
| ETIM 9.0                        | EC000140                  |
| IEC-amperage                    | 63 A                      |
| Number of poles                 | 4                         |
| Voltage according to EN 60309-2 | 200-250 V (50+60 Hz) blue |
| Clock hour position             | 9 h                       |
| Identification colour           | Blue                      |
| RAL-number                      | 7046                      |
| Degree of protection (IP)       | IP67                      |
| Connection system               | Screwed terminal          |
| Cable entry                     | Gland nut                 |
| Angle of plug                   | Straight                  |
| Material                        | Plastic                   |
| Contact material                | CuZn                      |
| Surface treatment contacts      | Nickel-plated             |

|                        |                      |
|------------------------|----------------------|
| a                      | 250 mm               |
| b                      | 115 mm               |
| K (cable Ø)            | 14,5-36 mm           |
| SW                     | 61 mm                |
| wire flexible          | 6-16 mm <sup>2</sup> |
| contact screws         | 200 Ncm              |
| connecting screws      | 200 Ncm              |
| strain relief          | 1500 Ncm             |
| dismantling length     | 100 mm               |
| stripping length       | 15-18 mm             |
| ambient temperature    | -25 – 40 °C          |
| temperature resistance | -25 – 80 °C          |

