
Item no.: 770-114

Product description: PLUG; WITH RELIEF HOUSING; 4 POLE; PIN SPACING 10 MM / 0.394 IN; 100% PROTECTED AGAINST MISMATING; CAGE CLAMP[®]S CONNECTION



Packing unit 25 pieces

Product group	20 (WINSTA)
pole count	4
Cross section from [mm ²]	0,5 mm ²
Cross section to [mm ²]	4 mm ²
Cross section from [AWG]	20 AWG
Cross section to [AWG]	12 AWG
Connection method	CONTACT CAGE CLAMP [®] CONNECTION
Number of strands	2
Measured voltage EN	400 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	25 A
Weight	24,991 g
Color	black
No. of connection Points	8
No. of potentials	4
Height	17 mm
Height	0,669 in
Width	44,6 mm
Width	1,756 in
Depth	75,9 mm
Depth	2,988 in
Strip length from	9 mm
Strip length to	9 mm
Strip length	0,35 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
770-114	CBCertificateVDE	DE1-29543	250/400	25	0,5-4
770-114	CCA	NL5566	400	25	0,5-4,0
770-114	cURus	E45171	600	20	12
770-114	DNV	E6188	400	25	4
770-114	GL	42875-02HH	400	25	4
770-114	KEMA	2060958.02	400	25	0,5-4,0
770-114	LR	02/20050(E3)	250	25	2,5
770-114	PRS	TE/1719/880590/08	400	25	0,5-4,0

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected