FEATURES AND SPECIFICATIONS

molex®

Voice Cabling System Disconnect and Connection Modules

Features and Benefits

The Molex Voice Cabling system is expressly designed for voice circuits, such as block cabling and PBX inter connections. The Molex voice cabling system provides a complete range of products to facilitate a complete voice cabling system, including; termination modules, mounting frames, distribution boxes, tester interfaces and over-voltage protection.

The Voice Cabling system is compatible with other popular cabling systems enabling integration with legacy systems for expansion or refurbishment projects.

Both disconnect and connection type modules are available for all voice applications, markets and regulatory requirements. The modules accommodate up to 10 pairs in a small footprint, enabling high density interconnection facilities.

- Distribution of voice applications
- Module is available in disconnect and connection format
- Standard 45° IDC contact
- Versatile can be used in indoor or outdoor applications
- Accepts cable diameter 0.4mm to 0.8mm
- Accommodates 2 wires
- Accepts KATT or LSA+ IDC tools

Technical Information

Disconnect Module

Housing: PBT Self extinguishing VO grade Contacts: Phosphor Bronze, Silver plated

Contact Resistance: < 5megaohms
Conformity: DIN 41611
Performance: Category 3

Module Dimmension: 22mm x 40mm x 125mm

Packaging: 10 per box Package Weight: 600g

Packade Dimensions: 220mm x 145mm x 60mm

Connection Module

Housing: PBT Self extinguishing VO grade Contacts: Phosphor Bronze, Silver plated

Contact Resistance: < 3megaohms
Conformity: DIN 41611
Performance: Category 3

Module Dimmension: 22mm x 40mm x 125mm

Packaging: 10 per box Package Weight: 600g

Packade Dimensions: 220mm x 145mm x 60mm





ORDERING INFORMATION

Order No.	Description
DCN-00001	10 Pair Disconnect Module
DCN-00002	10 Pair Connection Module