

SR cable and pipe seals

The SR glands are designed to seal cables or pipes between 4 and 100 mm (0.16 and 3.94") diameter.

The seal can be supplied cut to allow pre terminated cable to be installed. It is supplied with a center core providing a seal prior to cable installation. When the cable is inserted into the gland, simply tighten the compression bolts equally until cable is secure. Once complete the seal will provide an effective barrier against fire, water, dust, vermin, etc.

- Lloyds certified
- Pressure tested to 5 bar
- Gland is manufactured from stainless steel 316L and rubber
- Sleeves are supplied in electroplated mild steel



Ref	No of cables	Cable diameter min		Cable diameter max		Sleeve O/D		Weight inc. sleeve	
		mm	(inches)	mm	(inches)	mm	(inches)	Kg	(Oz)
SR 25	1	4	0.16	12	0.47	0.21	1.31	0.21	7.41
SR 38-1	1	11	0.43	24	0.94	0.33	1.90	0.33	11.64
SR 38-2	2	6	0.24	15	0.59	0.35	1.90	0.35	12.35
SR 38-3	4	6	0.24	12	0.47	0.33	1.90	0.33	11.64
SR 49	1	20	0.79	32	1.26	0.56	2.37	0.56	19.75
SR 62	1	30	1.18	42	1.65	0.88	2.87	0.88	31.04
SR 77	1	42	1.65	52	2.05	1.30	3.50	1.30	45.86
SR 102	1	52	2.05	70	2.76	2.30	4.50	2.30	81.13
SR 125	1	70	2.76	85	3.47	3.41	5.51	3.41	120.28
SR 150	1	85	3.35	100	3.94	4.11	6.63	4.11	144.98

Dimensions in millimeter and inches. Weights in kilograms and Oz.

Alternative cable configurations can be manufactured to suit specific customer requirements