

Mer om VDIB17716U01

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools

**VDIB17716U01****Actassi konnektor S-One Uskjermet Kat6 UTP 1 pk**

EI-nummer: 6915808

EAN: 3606480384486



 [Last ned produktdatablad for VDIB17716U01](#)

Karakteristikk**Teknisk informasjon**

Serie	Actassi
Product type	RJ45 nettverksuttak
Enhetens utseende	En enhet, ingen løse deler
Fargetone	Wire organizer: blue (ABS + PC) Connector: dark grey (ABS + PC)
Wiring Colour configuration	568 A/B
Forpakning	Individual bag
Antall pr. sett	Sett á 1

Komplementær

[In] merkestrøm	1.5 A at 25 °C
Voltage proof	1000 V AC/DC peak, between contacts
Contact resistance	20 mOhm
Isolasjonsmotstand	Initial insulation resistance: ≥ 500 MOhm at 100 V DC
AWG gauge	AWG 24...AWG 23
Durability	750 cycles
Koblingsdemping	≥ 35 dB at 30...100 MHz $\geq 75 - 20 \times \log(f)$ dB at 100...1000 MHz
Contact pins	8 pins of copper alloy and gold plated conforming to IEC 60603-7
Trekraft	50 N during 60 s
Transersalt konverteringstap	≥ 50 dB $\geq 68 - 20 \times \log(f)$ dB at 1...250000 kHz
Verktøy type	Uten verktøy
Kabelens ytre diameter	0,9...1,4 mm
Compatible LAN cable types	UTP
Nettverkskategori	6
Supported applications	1000BASE-T
Protocols	VoIP (Voice IP) PoE+ (Power over Ethernet) 4PPoE 100W (Power over Ethernet)
Produktkompatibilitet	RJ45 plug

Overføringsfrekvens	0..250 MHz
Type footprint	S-One DPM
Høyde	28 mm
Lengde	33 mm
Bredde	18 mm
Targeted region	Europe
Miljø	
Operational temperature range	-40...70 °C
Climatic category	40/070/21 (21 days)
Flammehemming	UL94-V0
Standarder	ANSI/TIA-568-C.2 IEC 60603-7-4 ISO/IEC 11801:2011 Ed.2.2 UL 1863
Packing Units	
Enhetsstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	8 g
Forpakning 1 høyde	1,9 cm
Forpakning 1 bredde	7,4 cm
Forpakning 1 lengde	5,8 cm
Offer Sustainability	
Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
REACH fri for SVHC	Ja
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Fri for giftige tungmetaller	Ja
Kvikksølv fri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-erklæring
Miljøinformasjon	Produktmiljøprofil
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Contractual warranty	
Garanti	18 months