



Art.nr	El.nummer	Farge	RAL
1489GA	3120027	GALVANISERT STÅL	-
1489B	3120028	SORT	9005

Generell informasjon

Type armatur	Pullert
Materiale	Galvanisert stål
Avdeknings materiale/optikk	PMMA, opal
Type lyskilde	LED modul AC
Lysstyring	Dimbar (Triac)
Netto / Brutto vekt armatur	7,8kg / 8,6kg
Forpakkingsstørrelse [cm]	15,5x15,5x55
LED	Lumens EDC/47C/10W/830/230V/A
Effekt W	10W
Armatureffekt	10W
Modul lumen	900lm
Lumen ut	252lm
Modul effektivitet	25,2lm/W
ULOR	44%
Fargetemperatur	3000K
Farvekonsistens (McAdam-Ellipse)	SDCM3
Fargegjengivelsesindeks	80
Beregnet levetid L70/B50 ved 25°C	50 000h
Energieffektivitetsindeks (EEL)	A+
Virkningsgrad	PF > 0,99
Ta nominel:	+25°C
Inrush current	46,1mA/500µs
Antall armaturer på automatsikring	B 10A: 42, B 16A: 68, C 10A: 70, C 16A: 115

Filer som kan lastes ned

Photometric LDT files, Photometric IES files, Manual, Sertifikater