



## Generell informasjon

Type armatur	Veggarmatur
Materiale	Pulver lakkert aluminiumstøp
Avdeknings materiale/optikk	Glass - herdet, klar
Type lyskilde	LED modul + driver
Lysstyring	Ikke dimbar
Netto / Brutto vekt armatur	4,56kg / 5,04kg
Forpakkingsstørrelse [cm]	20x17x28
2xLED moduler	Citizen CL-L 104-MC6L1-F5
Driver	OSRAM OTi DALI 15/220...240/1A0 LT2
Effekt W	12,8W
Armatureffekt	14,9W
Modul lumen	1220lm
Lumen ut	443lm
Modul effektivitet	95,3lm/W
Armatur Lumen/Watt	29,7lm/W
Fargetemperatur	3000K
Farvekonsistens (McAdam-Ellipse)	SDCM3
Fargegjengivelsesindeks	80
Beregnet levetid L70/B50 ved 25°C	50 000h
Energieffektivitetsindeks (EEI)	<b>A+</b>
Virkningsgrad	PF >0,95
Ta nominel:	+25°C
Inrush current	18,6A/240µs
Antall armaturer på automatsikring	<b>B 10A: 21, B 16A: 34, C 10A: 35, C 16A: 57</b>

## Filer som skal lastes ned

Photometric LDT files , Photometric IES files

