



**Patch cords category 5e and category 6 and 6<sub>A</sub>, U/UTP, F/UTP and S/FTP**

- Designed for cross connections at distribution points as well as connections of terminals with user outlet.
- Compatible with category 5e, 6 and 6<sub>A</sub>.
- Sequence 568B.
- F/UTP cables are resistant from mechanical damages, providing continuity of shielding.
- Five standard length options: 0.5 m, 1 m, 2 m, 3 m, 5 m.
- Equipped with special type RJ45 plugs fixed on the cable by means of moulding technology.



**MECHANICAL PARAMETERS:**

- Cable insulation material ..... PVC
- Plug case ..... UL94V2
- Plug contacts material ..... phosphor bronze
- Plug contacts plating ..... gold over nickel;
- Durability ..... > 750 cycles

**ELECTRICAL PARAMETERS:**

- Maximum voltage ..... > 125 V
- Maximum current ..... 1.5 A
- Insulation resistance ..... > 500 MΩ



**AVAILABLE TYPES OF PATCH CORDS:**

- U/UTP cat. 5e and cat. 6 patch cords are available in the following colours: grey, ivory, black, red, green, blue, yellow, orange, brown, purple and pink
- F/UTP cat. 5e and cat. 6 patch cords available in the following colours: grey, ivory, black, red, green, blue, yellow
- S/FTP cat. 6 patch cords available in the following colours: grey, ivory, black, red, green, blue, yellow

We also offer Cross Over, 6<sub>A</sub> S/FTP patch cords.



Patch cords category 5e and category 6

Patch cords	Copper cabling components
<b>DATA COMMUNICATION COMPONENTS AND SOLUTIONS</b>	