Commercial grade PVC sleeving Art.-No. 172-02163 | PVC250BK-PVC-BK | Details



• Commercial grade of PVC sleeving.

• Used as electrical insulation, physical protection and for decorative applications.

RoHS

More products in this product group: Insulating tubes >

Base Data

Application	It can be used as electrical insulation, physical protection and for decorative applications.
Colour	Black (BK)
Material	Polyvinylchloride (PVC)
Pack Cont.	50 m
Package Content in	bag
PART DESCRIPTION	PVC250BK-PVC-BK
Product Family	Commercial grade PVC sleeving
Product Group	Insulating tubes

Product Dimensions

Diameter (D)	25 mm
Inside Ø (ID)	25 mm
Wall (WT)	0.85 mm

Specifications

Elongation at break	270%
Flammability	self-extinguishing
Halogenfree	No
Operating Temperature - °C	-30 °C to +85 °C, intermittent +105 °C
Shelf Life	5 years
Specifications	RoHS
Tensile Strength	19 MPa
Test Method Tensile Strength	IEC 60684 P2

Logistics and Packaging

Country of Origin	GB
Customs Number	39173200
GTIN-13 / EAN	5022660176890
Storage Temperature	0 °C to +40 °C

More Information

ETIM 7.0 Key EC002254