

ENSTO

Sikringselement og klemmesett

LCK4-16-10A

Kode	LCK4-16-10A
GTIN	6438100310608
El nummer	3611621
Navn	Sikringselement og klemmesett LFB16-10A-R og SV15 (Al 10-35 / Cu 1.5-25)
Beskrivelse	LCK4-16-10A inneholder tre klemmer KE10.1, en nøytral klemme KE10.3 og en sikringholder LFB16-10A. Nøytral klemme KE10.3 er utstyrt med 16 mm ² jordledning på 0,35 m med en kabelsko på den andre enden. 10A sikring er inkludert i LFB16-10A-R. KE10.1 & KE10.3 klemmer passer for kabler 10-35 mm ² Al eller 1.5-25 mm ² Cu.
Selger	Ensto Finland Oy



Technical specification

Grunnleggende

Inkludert: LFB16-10A-R + 3x KE10.1 + 1x KE10.3

Sertifikater

Standard merking: IEC 60269-1:2006, IEC 61238-1:2003

Mål

Avgreningsleder mm ² :	4 mm ²
Leder tverrsnitt Al:	10 ... 35 mm ²
Leder tverrsnitt Cu:	1,5 ... 35 mm ²
Lederdiameter:	1,7 ... 9 mm
Weight:	0,375 kg

Elektriske verdier

Sikring: ≤ 16 A

Funksjoner

Leder inkludert: 3x KE10.1, 1x KE10.3

Others

ETIM Class: EC000899

ETIM Technical specification

etim

Type of fuse insert: D-system

Type of fuse holder: Screwable

Type of indication element for defect indication: Other

Connectable conductor cross section fine-strand without cable end sleeve: 1,5 ... 35 mm²

Connectable conductor cross section multi-wired: 1,5 ... 35 mm²

Rated current In: 16 A

Rated voltage: 400 V

Type of electrical connection 1: Screw connection

Type of electrical connection 2: Screw connection

Mounting method: Direct mounting

Material insulation body: Thermoplastic

Colour: Black

Packaging

Pallet package

Package size: 540 pcs

Depth: 1200 mm

Width: 800 mm

Height: 1112 mm

Default package

Package size: 10 pcs

Depth: 383 mm

Width: 258 mm

Height: 173 mm

Weight: 4,078 kg

Volume: 17,094822 l