


Reducing Coupling 40 × 25

Item # 0711060400250A



Technical Drawing Dimensions

Plasson Australia Code	Product Code	d1 [mm]	d [mm]	H [mm]	E [mm]	E1 [mm]	l [mm]	l1 [mm]	Unit Per Carton	Weight [g]
7110016	0711060400250A	25	40	156	82	54	84	58	90	219

Product Specifications

Product Features

Product Code	0711060400250A	Product Components	2 Split Rings, 2 Nuts, 2 seals
Product Name	Reducing Coupling 40 × 25	Split Ring Material	Polyacetal
Nominal Diameter Mains [mm]	40	Seal Material	NBR
Nominal Diameter Outlet [mm]	25	Nut Material	Polypropylene, high-grade copolymer.
Weight [g]	219	Unit Per Carton	90
Body Material	Polypropylene, high-grade copolymer.	Pressure Rating Water	PN 16

Product Specifications

Product Features

Standards

ISO 17885, AS/NZS 4129, ISO 7/1, BS 21, DIN 2999, UNI 9561, NEN 3258, AS 1722, DIN 8076

Chemical Resistance

Polyacetal split rings and NBR o-rings, suitable for water, are supplied as standard. CPVC split rings and EPDM or FPM o-rings and seals are available. For aggressive chemical applications, the end user is advised to test suitability.

Operating Temperatures

Maximum temperature of use for fittings and valves is the same as that for polyethylene pipe and they are not intended for use in hot water applications. They will withstand sub-zero temperatures.

