## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: LEDVANCE GmbH, Parkring 29-33, 85748 Garching, DE

Model identifier: AC44150

_	•			
Type	Λt	liont	COLL	rca.
IVDC	v	HIGHL	30 U	ı cc.

LED	Non-directional or directional:	NDLS
G5		
NMLS	Connected light source (CLS):	No
No	Envelope:	-
No		
No	Dimmable:	No
	G5  NMLS  No  No	directional:  G5  NMLS Connected light source (CLS):  No Envelope:  No

## **Product parameters**

Froduct parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		26	Energy efficiency class	E			
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		3 600 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000			
On-mode power (P <sub>on</sub> ), expressed in W		26,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00			
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80			
Outer dimen-	Height	1 449	Spectral power dis-	See image			
sions without	Width	19	tribution in the	in last page			
separate con- trol gear, light- ing control	Depth	19	range 250 nm to 800 nm, at full-load				

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,434		
		nates (x and y)	0,403		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	80	Survival factor	0,90		
the lumen maintenance factor	0,70				

(a)'-': not applicable; (b)'-': not applicable;

