


## Reducing Coupling 40 × 32

Item # 0711060400320A



### Technical Drawing Dimensions

Plasson Australia Code	Product Code	d1 [mm]	d [mm]	H [mm]	E [mm]	E1 [mm]	l [mm]	l1 [mm]	Unit Per Carton	Weight [g]
7110017	0711060400320A	32	40	156	82	64	84	67	90	245

#### Product Specifications

#### Product Features

Product Code	0711060400320A	Product Components	2 Split Rings, 2 Nuts, 2 seals
Product Name	Reducing Coupling 40 × 32	Split Ring Material	Polyacetal
Nominal Diameter Mains [mm]	40	Seal Material	NBR
Nominal Diameter Outlet [mm]	32	Nut Material	Polypropylene, high-grade copolymer.
Weight [g]	245	Unit Per Carton	90
Body Material	Polypropylene, high-grade copolymer.	Pressure Rating Water	PN 16

#### Product Specifications

#### Product Features

#### Standards

ISO 17885, AS/NZS 4129, ISO 7/1, BS 21, DIN 2999, UNI 9561, NEN 3258, AS 1722, DIN 8076

#### Chemical Resistance

Polyacetal split rings and NBR o-rings, suitable for water, are supplied as standard. CPVC split rings and EPDM or FPM o-rings and seals are available. For aggressive chemical applications, the end user is advised to test suitability.

#### Operating Temperatures

Maximum temperature of use for fittings and valves is the same as that for polyethylene pipe and they are not intended for use in hot water applications. They will withstand sub-zero temperatures.

