

# ENSTO

## Arbeidsjordingsklemme

SEW30



Kode	SEW30
GTIN	6438100320072
El nummer	2850344
Navn	Arbeidsjordingsklemme MV CC 50-157 mm <sup>2</sup>
Beskrivelse	SEW30 brukes som tilkobling for midlertidig jording på BLL/BLX. Silikonfett på klemmens tenner gjør den vanntett. Den nominelle tykkelsen på linens isolasjon kan være mellom 2,3-4,0 mm.
Selger	Ensto Finland Oy

## Teknisk spesifisering

### Sertifikater

Standard merking: EN 50397-2

### Mål

Hoved leder mm <sup>2</sup> :	50-157 mm <sup>2</sup> AlMgSi
Lengde:	236 mm
Bredde:	177 mm
Høyde:	129 mm
Lederdiameter:	11,5 ... 22,5 mm
Net Weight:	1,39 kg

### Mekanisk

Tiltrekningsmoment: 35 Nm

### Annet

ETIM Class: EC001062

## ETIM Teknisk spesifisering

### etim

Material main conductor: Aluminium

Material branch conductor:	Aluminium
Clamping channel opening main conductor:	Both sides open
Clamping channel opening branch conductor:	Both sides open
Surface protection:	Bare
Type of connection:	Insulation piercing connector IPC

## Emballasje

---

### Carton (Standardpakke)

Pakkestørrelse:	6 pcs
Dybde:	380 mm
Bredde:	260 mm
Høyde:	130 mm
Vekt:	8,84 kg
Volum:	12,844 l

### Pallepakke

Pakkestørrelse:	378 pcs
Dybde:	1200 mm
Bredde:	800 mm
Høyde:	1190 mm
Vekt:	576,92 kg
Volum:	1142,4 l