

ENSTO

SLW36

Klemmer og bøyer for AUS

Kode	SLW36
GTIN	6438100304577
El nummer	2874650
Navn	Klemmer og bøyer for AUS AUS klemme BLX/BLL 50-157mm ²
Beskrivelse	Brukes som AUS-klemme for belagte liner. Det er også mulig å koble til arbeidsjording. Klemme er laget av korrupsjonsresistent aluminium og boltene er av rustfritt stål.



Teknisk spesifikasjon

Dimensjoner

Vekt:	0.49 kg
Lederdiameter mm:	12.7-22.3
Hoved leder mm ² :	PAS/BLL-T 50-157
Avgreningsleder mm ² :	Al 50-157

Mekanisk

Tiltrekningsmoment:	40 Nm
---------------------	-------

Rangeringer

ETIM 7:	EC001062 Branch terminal
---------	--------------------------

Specification

Use:	Used when a branching or transformer connection to a live insulated conductor is required. By applying the stirrup first and then connecting to its loop any possible arcing damage to the conductor is avoided.
------	--

Construction:

Construction:	Component	Material
	Body	Corrosion resistant aluminium alloy, tensile strength 300 N/mm ²
	Screws	Stainless steel / Aluminium
Installation:	The insulation of the conductor need not to be removed. The live-line clamp can be installed with standard live-line sticks. The screws have to be tightened to torque of 40 Nm.	
Tools required:	Live-line stick CT48.64	
Markings:	SLW 36, Ensto 50-157 mm ² 40 Nm week/year of manufacture	
Standard:	EN 50397-2	

ETIM

ETIM

Nominal cross section main conductor, SM: 50 ... 157 mm²

Nominal cross section main conductor, SE: 50 ... 157 mm²

Material main conductor: Aluminium

Nominal cross section branch conductor, SE/RE: 50 ... 157 mm²

Clamping channel opening main conductor: Both sides open

Surface protection: Bare

Terminal insulated: false

Material branch conductor: Aluminium

Type of connection: Screwed connection

Clamping channel opening branch conductor: Both sides open

Nominal cross section branch conductor, SM/RM: 50 ... 157 mm²

Pakningsstørrelse

Pakke

Unit: PCS

Size: 24

Length: 400 mm

Width: 265 mm

Height: 220 mm

Weight (net): 11.86 kg

Weight (brt): 12.1 kg

Volume: 0.0233

Pallet package

Unit: PCS

Size: 864

Length:	1200 mm
Width:	800 mm
Height:	1020 mm
Weight (net):	426.82 kg
Weight (brt):	447 kg
Volume:	0.9792