



SL4/SL7 SIGNAL TOWERS
171367



Overview



Specifications



Resources



Contact



Photo is representative




Photo is representative

171367

Eaton Moeller® series SL4 Strobe light module; blue



How to buy




Photo is representative




Photo is representative



Designed to work together

Discover other Eaton products and accessories built to enhance this product.



171297

Eaton Moeller® series SL4 Base module;100-mm aluminum tube and foot



171303

Eaton Moeller® series SL4 Base module;for vertical mounting on one sides



171302

Eaton Moeller® series SL4 Base module;external fixing holes



171305

Eaton Moeller® series SL4 Base module;100 mm aluminum tube

[View more](#)[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

PRODUCT NAME	Eaton Moeller® series SL4 Strobe light module
--------------	---

CATALOG NUMBER	171367
----------------	--------

Product specifications

>

MODEL CODE	SL4-FL230-B
------------	-------------

EAN	4015081678983
-----	---------------

PRODUCT LENGTH/DEPTH	43 mm
----------------------	-------

PRODUCT HEIGHT	75 mm
----------------	-------

PRODUCT WIDTH	43 mm
---------------	-------

PRODUCT WEIGHT	0.044 kg
----------------	----------

CERTIFICATIONS

CSA-C22.2 No. 94-91
IEC/EN 60529
UL 508
UL File No.: E29184
CSA Class No.: NKCR7
CE
UL report applies to both US and Canada
IEC/EN 60947-5-1
CSA-C22.2 No. 14-10
Certified by UL for use in Canada
UL Category Control No.: NKCR
UL

PRODUCT SPECIFICATIONS

PRODUCT CATEGORY	SL signal towers
------------------	------------------

ENCLOSURE COLOR	Black
-----------------	-------

RADIATION ANGLE	360 °
-----------------	-------

LEAKAGE CURRENT	0.003 A
-----------------	---------

OUTSIDE DIAMETER	43 mm
------------------	-------

LIGHT MODULES	LED
---------------	-----

RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN	230 V
--	-------

FLASHING FREQUENCY	1.4 Hz
--------------------	--------

LIGHT TYPE	Strobe light
------------	--------------

DEGREE OF PROTECTION	NEMA 13 IP66
----------------------	-----------------

OVERVOLTAGE CATEGORY	III
RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN	0 V
RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX	0 V
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	240 V
POLLUTION DEGREE	3
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
COLOR	Blue
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
CONNECTION TO SMARTWIRE-DT	No
FUNCTIONS	Flash light
MATERIAL	Cap: Polycarbonate (PC) Enclosure: Polycarbonate (PC)
LAMP TYPE	LED
LIFESPAN, ELECTRICAL	100,000 h
AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
TYPE	Strobe light module
MOUNTING POSITION	As required
CURRENT CONSUMPTION	0.1 A, at 230/240 V AC
SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27 11 ms Mechanical, According to IEC/EN 60068-2-27
VOLTAGE TYPE	AC
NUMBER OF MODULES	Max. 10 (with base for mounting on both sides) Max. 5 (with standard base)
RATED INSULATION VOLTAGE (UI)	250 V

Brochures

Catalogs

Certification reports

Drawings

eCAD model

Installation instructions

Installation videos

mCAD model



[Contact me](#)

171367

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

