

ENSTO

Polymeric stay wire insulator

SDI69

Code	SDI69
GTIN	6438389023473
Name	Polymeric stay wire insulator 24 kV
Description	Polymeric stay wire insulator is suitable for installation in stay wires 25-70 mm ² . Conforms with standard SFS 3741-H24. Creepage distance is 160 mm.
Vendor	Ensto Finland Oy

Technical specification

Dimensions

Length:	278 mm
Width:	133 mm
Height:	133 mm
Weight:	0.793 kg
Creepage distance:	160 mm

Electrical values

Highest system voltage:	24 kV
Wet power frequency withstand voltage:	≥ 24 kV

Mechanical

Max. continuous load:	35 kN
SMFL:	130 kN

Others

ETIM Class:	EC003514
-------------	----------

ETIM Technical specification

etim

Model:	Tension insulator
Rated voltage:	24000 kV

Length:	278 mm
Diameter:	133 mm
Weight:	0.793 kg
Wet power frequency withstand voltage:	24 kV

Packaging

Carton (Default package)

Package size:	12 pcs
Depth:	395 mm
Width:	320 mm
Height:	280 mm
Weight:	9.933 kg
Volume:	35.392 l

Pallet package

Package size:	216 pcs
Depth:	1200 mm
Width:	800 mm
Height:	1045 mm
Weight:	198.794 kg
Volume:	1003.2 l