



S LUB 100XL LT

For Low Temperature application Winter grade

TECHNICAL INFORMATION

S LUB 100XL LT is a special lubricant, **high performance**, for fiber optical installation for min and micro cable for blowing machine cable installer. It's a water emulsion of different kind of polymers.

S LUB 100XL LT is a water base product with high lubricant efficiently. It's reduce dramatically the friction. **S LUB 100XL LT** is white liquid little bit viscosity.

S LUB 100XL adhere perfectly at the cable surface or at the internal surface of the pipe. It's left a very tiny film of lubricant and does not make the glue effect. The feeling is like "never dry"

Product Use: Cable and Duct Prelubrication

S LUB 100XL LT has the same base products of **S LUB 100** but is much more performance due a specific additives very active in this field to reduce the friction.

S LUB 100XL LT has a freezing point less than -10°C

Suggested Uses quantities for 1.000 mt

internal duct diam \varnothing mm	Quantities of product	How much the duct must be fill of the product (different kind of measure for the same quantities)
4 mm	5 ml	≈ 30 cm
8 mm	10 ml	≈ 20 cm
12 mm	15 ml	≈ 15 cm

The real quantities could change due to a condition of the duct or how is pipe long difficult



CARIMA S.r.l. – C.F. e P. IVA 06727370154
Via dei Brughi, 30/31 – 20060 Gessate (MI) - Italy
Tel. e fax +39 02 9538.4225 - fax +39 02 7005.8164 - cell uff +39 348 6003.588
www.carima.biz info@carima.biz

Uses:

Shake the bottle before use, then put the product inside in the duct. Then pre-lubricant the pipe with a little piece of sponge pushed by air compress.

The product is also suitable for blowing machine with oil dispenser to lubricating the fiber during the pushing.

The **S LUB 100XL LT**, also can be useful to lubricate the fiber optic before or after blowing machine. It's depend on the appliance with iron wheel or with rubber wheel.

Technical Specification:

Aspect	White liquid tiny viscosity
Odour	characteristic
Viscosity	30 sec. Ford cup diam. mm 4 at 20C°
Spefigic gravity	1,030 +- 0,03 gr/cm ³
pH	7,5 +- 0,5
Inflammability	non infiammabile
Temperature	-10° + 70° C.

CONFEZIONI

Cod. **VSLUBLT100XL.05** bottle of 500 ml in a card box of 12 pcs

Cod. **VSLUBLT100XL.1** bottle of 1 lt in a card box of 15 pcs

Cod. **VSLUBLT100XL.5,10,20, 25** in a tank of Kg 5, 10,20 e 25