


Technical data sheet for:

## EBM 32, 40 und 50



### General data

<b>Item</b>	Splitable connector - EBM 32, EBM 40, EBM 50
<b>Description</b>	Splitable connectors are used for the gas-and watertight sealing of connections between split duct (KKHR) and PE-duct.
<b>Package unit</b>	12 Pcs.

### Technical data

Quality	Value	Unit
<b>Material</b>	PolyVenylChlorid - Unplastinized PVC-U	
<b>Dimension</b>	EBM 32: d = 32; L = 125;	mm
	EBM 40: d = 40; L = 125;	
	EBM 50: d = 50; L = 125;	
<b>Pressure</b>	0,5 (permanent gas- and watertight)	bar
	10 / 30	bar / min
<b>Tensile strength</b>	EBM 32: min. 1300	N
	EBM 40: min. 1300	
	EBM 50: min. 1500	
<b>Pressing operation clamp on case</b>	min. 1550	N

**gabocom is certified by the quality system following DIN EN ISO 9001:2008**

gabo Systemtechnik GmbH  
 Am Schaidweg 7  
 94559 Niederwinkling  
 Germany

Phone 0049 (0)9962 950 200  
 Fax 0049 (0)9962 950 202  
 info@gabocom.de  
 www.gabocom.de

Editor: PW  
 Release: MK  
 Edition: 14.11.2011

No responsibility is taken for the correctness, currency and completeness of details and information.  
 Liability for damages is excluded.