Split ducts

32 / 40 / 50 / 110 / 125



Split ducts

Product advantages

- The split ducts KKHR were developed by gabocom for the pressure-tight repair of empty ducts or ducts occupied with cables or speed•pipe®.
- They are suitable for the gas- and water-tight sealing of blow-in points.
- They consist of two half shells manufactured out of high-quality PVC-U.
- The easy installation facilitates the branching off pipeline routes.

Fittings

- Connectors 7
- Assembly tools 8

Ordering data

Term	D×s (mm)	Length (mm)	Gas- and water-tight up to	Pcs. / unit	Pcs. / pallet	Item no.
KKHR 32	32×1.8	2000	0.5 bar permanent (10 bar / 30 min.)	2	84	12195
KKHR 40	40×1.9	2000	0.5 bar permanent (10 bar / 30 min.)	2	68	09956
KKHR 50	50×2.4	2000	0.5 bar permanent (10 bar / 30 min.)	3	51	09957
KKHR 110	110×3.2	2000	0.5 bar	3	78	14149
KKHR 110	110×3.2	6000	0.5 bar	3	78	04709
KKHR 125	125×3.7	3000	0.5 bar	4	52	05298
KKHR 125	125×3.7	6000	0.5 bar	4	52	05299