RUNPOSTICKS Comfort Package 19-parts

Pulling aid for not guided pipelines

Item no.: 10020







Extreme bending radius



DATA	
ITEM NO.:	10020
WEIGHT NET	1,02 kg
DIMENSION	L 1010 mm x B 105 mm x H 45 mm
MATERIAL	Basalt rods, plastic-coated
THREAD	RTG Ø 6 mm
EAN-CODE	9120045473100

DESCRIPTION

The new basalt technology allows extreme bending radii, however, the rods retain high dimensional stability. All connections have a RUNPOTEC RTG \varnothing 6 mm thread, have no butt edges or thread transitions. Objects weighing up to 2.5 kg can be held with the magnet. In combination with the magnet, the ball chain enables targeted locating or guiding to wall openings. In addition, the Comfort package includes the special sliding hook and can easily overcome obstacles up to 8 cm high thanks to the tilt function. The shockproof LED lamp also included has a very high luminosity and extremely long illumination time due to its AAA Duracell battery. All accessories can be perfectly stored in the practical storage bag with carrying strap.

Optimal area of application: suspended ceilings, cable ducts, hollow walls, retroactive cabling for non-routed cables, underfloor shafts, various bushings and much more.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.RUNPOTEC.com.

Scope of supply: 5×1 m RUNPOSTICKS red (hard) \emptyset 7,5 mm, 3×1 m RUNPOSTICKS black (medium) \emptyset 5,5 mm, 2×1 m RUNPOSTICKS yellow (soft) \emptyset 4,5 mm, $1 \times RG7$ RUNPOGLEITER, $1 \times extra$ strong magnet, $1 \times extra$ ball chain, $1 \times extra$ with ring, $1 \times extra$ strong thread, $1 \times extra$ storage bag, $1 \times extra$ special sliding hook, $1 \times extra$ shockproof LED lamp

ADVANTAGES

- 30% higher load capacity due to basalt fibre technology
- Plastic-coated therefore no penetration of the fibres under the skin
- Extreme bending radius
- Ultra strong magnet
- Sliding hook with tilt function
- Shockproof LED Lamp
- Practical storage bag
- Stainless steel connection press fitted and bonded

