

**45182008**

## Insulated flexible copper bar 8x20x1 L=2000mm



Flexible copper bars are mainly used for providing the power connections between busbars and the disconnection devices.

### Strong points

- Easy setup
- Increased safety without crimped connections
- Conductor

### General characteristics

- Width from 9 to 100 mm.
- Copper layer thickness from 0.8 to 1 mm.
- Length of 2 m.
- Conductor: Layers of electrolytic copper Cu/ETP, final annealing state.

### Compliance with standards

- VDE 207 Y16
- BS 6746
- NF A 51-050
- VDE 207 YM4
- DIN 40050

### Link to the reference

### Classification

UNSPSC	26121634
ETIM Class	EC001522
IGCC	1786

### Commerce

Effective date	2000-08-01
Offer Life Cycle Code	40
Country of origin	DE

### ETIM - Electrical characteristics

Rated current In [A]	488
----------------------	-----

### ETIM - Mechanical characteristics

Length [mm]	2000
Width [mm]	20
Height [mm]	1
Surface protection	Other

### ETIM - Technical features

Model	Other
Flexible	Yes

### Logistics

GTIN/EAN	3596031224692
Customs number	7409190000
Price unit	PC
Weight of the packing unit [kg]	3.17
Length of the packing unit [m]	0.008
Width of the packing unit [m]	0.02
Depth of the packing unit [m]	2

### Norms

Conformity to standards	IEC
-------------------------	-----

### SYSTEME

ReferenceLabel	45182008   CU.SPLE.ISO.8X20X1 L=2M
----------------	------------------------------------

### Technical Characteristics

Length of the product unit [mm]	2000
Width of the product unit [mm]	20
Depth of the product unit [mm]	1
Weight [kg]	3.17
Height [mm]	20
Length	2000
Model	Insulated Flexible Copper Bar
Thickness	1
Number of layers	8