

45183202

Insulated flexible copper bar 2x32x1 L=2000mm



Flexible copper bars are mainly used for providing the power connections between busbars and the disconnection devices.

Strong points

- Easy setup
- Increased safety without crimped connections
- Conductor

General characteristics

- Width from 9 to 100 mm.
- Copper layer thickness from 0.8 to 1 mm.
- Length of 2 m.
- Conductor: Layers of electrolytic copper Cu/ETP, final annealing state.

Compliance with standards

- VDE 207 Y16
- BS 6746
- NF A 51-050
- VDE 207 YM4
- DIN 40050

Link to the reference

Classification

UNSPSC	26121634
ETIM Class	EC001522
IGCC	1786

Commerce

Effective date	2000-08-01
Offer Life Cycle Code	40
Country of origin	DE

ETIM - Electrical characteristics

Rated current In [A]	331
----------------------	-----

ETIM - Mechanical characteristics

Length [mm]	2000
Width [mm]	32
Height [mm]	1
Surface protection	Other

ETIM - Technical features

Model	Other
Flexible	Yes

Logistics

GTIN/EAN	3596031224784
Customs number	7409190000
Price unit	PC
Weight of the packing unit [kg]	1.5
Length of the packing unit [m]	0.002
Width of the packing unit [m]	0.032
Depth of the packing unit [m]	2

Norms

Conformity to standards	IEC
-------------------------	-----

SYSTEME

ReferenceLabel	45183202 CU.SPLE.ISO.2X32X1 L=2M
----------------	------------------------------------

Technical Characteristics

Length of the product unit [mm]	2000
Width of the product unit [mm]	32
Depth of the product unit [mm]	1
Weight [kg]	1.5
Height [mm]	32
Length	2000
Model	Insulated Flexible Copper Bar
Thickness	1
Number of layers	2