

**45183210**

## Insulated flexible copper bar 10x32x1 L=2000mm



Flexible copper bars are mainly used for providing the power connections between busbars and the disconnection devices.

### Strong points

- Easy setup
- Increased safety without crimped connections
- Conductor

### General characteristics

- Width from 9 to 100 mm.
- Copper layer thickness from 0.8 to 1 mm.
- Length of 2 m.
- Conductor: Layers of electrolytic copper Cu/ETP, final annealing state.

### Compliance with standards

- VDE 207 Y16
- BS 6746
- NF A 51-050
- VDE 207 YM4
- DIN 40050

### Link to the reference

### Classification

|            |          |
|------------|----------|
| UNSPSC     | 26121634 |
| ETIM Class | EC001522 |
| IGCC       | 1786     |

### Commerce

|                       |            |
|-----------------------|------------|
| Effective date        | 2000-08-01 |
| Offer Life Cycle Code | 40         |
| Country of origin     | DE         |

### ETIM - Electrical characteristics

|                      |     |
|----------------------|-----|
| Rated current In [A] | 777 |
|----------------------|-----|

### ETIM - Mechanical characteristics

|                    |       |
|--------------------|-------|
| Length [mm]        | 2000  |
| Width [mm]         | 32    |
| Height [mm]        | 1     |
| Surface protection | Other |

### ETIM - Technical features

|          |       |
|----------|-------|
| Model    | Other |
| Flexible | Yes   |

### Logistics

|                                 |               |
|---------------------------------|---------------|
| GTIN/EAN                        | 3596031224845 |
| Customs number                  | 7409190000    |
| Price unit                      | PC            |
| Weight of the packing unit [kg] | 6.1           |
| Length of the packing unit [m]  | 0.001         |
| Width of the packing unit [m]   | 0.032         |
| Depth of the packing unit [m]   | 2             |

### Norms

|                         |     |
|-------------------------|-----|
| Conformity to standards | IEC |
|-------------------------|-----|

### SYSTEME

|                |                                     |
|----------------|-------------------------------------|
| ReferenceLabel | 45183210   CU.SPLE.ISO.10X32X1 L=2M |
|----------------|-------------------------------------|

### Technical Characteristics

|                                 |                               |
|---------------------------------|-------------------------------|
| Length of the product unit [mm] | 2000                          |
| Width of the product unit [mm]  | 32                            |
| Depth of the product unit [mm]  | 1                             |
| Weight [kg]                     | 6.1                           |
| Height [mm]                     | 32                            |
| Length                          | 2000                          |
| Model                           | Insulated Flexible Copper Bar |
| Thickness                       | 1                             |
| Number of layers                | 10                            |