

45189006

Insulated flexible copper bar 6x100x1 L=2000mm



Flexible copper bars are mainly used for providing the power connections between busbars and the disconnection devices.

Strong points

- Easy setup
- Increased safety without crimped connections
- Conductor

General characteristics

- Width from 9 to 100 mm.
- Copper layer thickness from 0.8 to 1 mm.
- Length of 2 m.
- Conductor: Layers of electrolytic copper Cu/ETP, final annealing state.

Compliance with standards

- VDE 207 Y16
- BS 6746
- NF A 51-050
- VDE 207 YM4
- DIN 40050

Link to the reference

Classification

| | |
|------------|----------|
| UNSPSC | 26121634 |
| ETIM Class | EC001522 |
| IGCC | 1786 |

Commerce

| | |
|-----------------------|------------|
| Effective date | 2000-08-01 |
| Offer Life Cycle Code | 40 |
| Country of origin | DE |

ETIM - Electrical characteristics

| | |
|----------------------|------|
| Rated current In [A] | 1460 |
|----------------------|------|

ETIM - Mechanical characteristics

| | |
|--------------------|-------|
| Length [mm] | 2000 |
| Width [mm] | 100 |
| Height [mm] | 1 |
| Surface protection | Other |

ETIM - Technical features

| | |
|----------|-------|
| Model | Other |
| Flexible | Yes |

Logistics

| | |
|---------------------------------|---------------|
| GTIN/EAN | 3596031225125 |
| Customs number | 7409190000 |
| Price unit | PC |
| Weight of the packing unit [kg] | 11.7 |
| Length of the packing unit [m] | 0.006 |
| Width of the packing unit [m] | 0.1 |
| Depth of the packing unit [m] | 2 |

Norms

| | |
|-------------------------|-----|
| Conformity to standards | IEC |
|-------------------------|-----|

SYSTEME

| | |
|----------------|-------------------------------------|
| ReferenceLabel | 45189006 CU.SPLE.ISO.6X100X1 L=2M |
|----------------|-------------------------------------|

Technical Characteristics

| | |
|---------------------------------|-------------------------------|
| Length of the product unit [mm] | 2000 |
| Width of the product unit [mm] | 100 |
| Depth of the product unit [mm] | 1 |
| Weight [kg] | 11.7 |
| Height [mm] | 100 |
| Length | 2000 |
| Model | Insulated Flexible Copper Bar |
| Thickness | 1 |
| Number of layers | 6 |