

# Specifications

## Eaton EP-401370

Eaton Touch panel XV-303, 24 V DC, 15.6 Inch, 2 x Ethernet, 1 x RS-232, 1 x RS-485, 1 x CAN, Linux, Capacitive multi touch, PLC



Photo is representative



### General specifications

<b>PRODUCT NAME</b>	Eaton XV-303 Touch panel
<b>CATALOG NUMBER</b>	EP-401370
<b>MODEL CODE</b>	XV-303-15-C00-A00-2C
<b>EAN</b>	7640130100244
<b>PRODUCT LENGTH/DEPTH</b>	403.7 mm
<b>PRODUCT HEIGHT</b>	67 mm
<b>PRODUCT WIDTH</b>	254.9 mm
<b>PRODUCT WEIGHT</b>	3.2 kg
<b>CERTIFICATIONS</b>	CUL CE Certified by UL for use in Canada IEC/EN 61000-6-2 IEC/EN 61000-6-4 UL UL 61010-2-201 UL File No.: E205091

Features & Functions	
ENCLOSURE MATERIAL	Insulated material
FITTED WITH:	Color display 1 x RS232 (built-in interface) Printer output SW interfaces 1 x RS485 (built-in interface) 1 x USB host 2.0 (built-in interface) Message system (incl. buffer and confirmation) Message indication Recipes 2 x Ethernet 10/100 Mbps (built-in interface) 1 x CAN (built-in interfaces)
FUNCTIONS	Process value representation (output) possible Additional software components, loadable Process default value (input) possible

Ambient conditions, mechanical	
SHOCK RESISTANCE	15 g, 11 ms, Mechanical
VIBRATION RESISTANCE	9 - 60 Hz, $\pm 0.15$ mm 5 - 9 Hz, $\pm 3.5$ mm 60 - 150 Hz, $\pm 2$ g

General	
BATTERY RUNTIME	Back-up of real-time clock: BR 2330, non-replaceable (soldered)
DEGREE OF PROTECTION	NEMA 4X NEMA 12 IP20, rear (according to EN 60529-1)
DEGREE OF PROTECTION (FRONT SIDE)	NEMA 12 IP65
FUSE TYPE	Built-in fuse (not accessible)
LIFESPAN	50,000 h (Service life of back-lighting)
MODEL	Plastic enclosure and glass panel in plastic frame
MOUNTING METHOD	Flush mounting Flush mounting - Mounting plate: min. 1.5 mm (0.06"), max. 4 mm Flush mounting - Inclination from vertical: $\alpha \leq \pm 10^\circ$ (if using natural convection) Flush mounting - Clearance: Width x Height $\geq 50$ mm (1.97"), Depth $\geq 20$ mm (0.79") Flush mounting - Inclination from vertical: $\alpha \leq \pm 45^\circ$ at operating temperature $\leq 45^\circ\text{C}$ (113°F) (if using natural convection)
POTENTIAL ISOLATION	Power supply: no
PROTECTION AGAINST POLARITY REVERSAL	Yes
PRODUCT CATEGORY	XV-300
ROHS CONFORMITY	Yes
SOFTWARE	XSOFT-CODESYS-3, PLC-Programming software, Engineering GALILEO, Visualization software, Engineering XSOFT-CODESYS-3, Visualization software, Engineering
TYPE	Control panel with PLC and 2nd Ethernet port
VOLTAGE TYPE	DC

Climatic environmental conditions	
AIR PRESSURE	795 - 1080 hPa (operation)
AMBIENT OPERATING TEMPERATURE - MIN	0 °C

<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	50 °C
<b>AMBIENT STORAGE TEMPERATURE - MIN</b>	-20 °C
<b>AMBIENT STORAGE TEMPERATURE - MAX</b>	60 °C
<b>CLIMATIC PROOFING</b>	Damp heat, constant, to IEC 60068-2-3 Cold to EN 60068-2-1 Dry heat to IEC 60068-2-2
<b>ENVIRONMENTAL CONDITIONS</b>	Condensation: Non-condensing
<b>OPERATING TEMPERATURE - MIN</b>	0 °C
<b>OPERATING TEMPERATURE - MAX</b>	50 °C
<b>RELATIVE HUMIDITY</b>	10 - 95 % (non-condensing)

Electro magnetic compatibility	
<b>EMITTED INTERFERENCE</b>	According to IEC/EN 61000-6-4
<b>INTERFERENCE IMMUNITY</b>	According to EN 61000-6-2
<b>VOLTAGE DIPS</b>	5 ms from undervoltage (19.2 V DC) ≤ 10 ms from rated voltage (24 V DC)

Electrical rating	
<b>PERMISSIBLE VOLTAGE</b>	35 V DC (for a duration of < 100 ms) 18.0 - 31.2 V DC, absolute with ripple 18 - 31.2 V DC, battery powered (rated operating voltage -25 %/+30 %) 19.2 - 30 V DC, effective (rated operating voltage -20 %/+25 %)
<b>POWER CONSUMPTION</b>	19.1 W 16 W typ. Max. 21.6 W
<b>RATED OPERATIONAL VOLTAGE</b>	24 V DC (power-supply - safety extra low voltage)
<b>SUPPLY VOLTAGE AT AC, 50 HZ - MIN</b>	0 VAC
<b>SUPPLY VOLTAGE AT AC, 50 HZ - MAX</b>	0 VAC
<b>SUPPLY VOLTAGE AT DC - MIN</b>	19.2 VDC
<b>SUPPLY VOLTAGE AT DC - MAX</b>	30 VDC

Communication	
<b>INTERFACES</b>	10/100 Mbps Ethernet connection RS485 (not galvanically isolated, 9-pin SUB-D plug, UNC) CAN (not galvanically isolated, 9-pin SUB-D plug, UNC) RS232 (not galvanically isolated, 9-pin SUB-D plug, UNC) USB 2.0 host (not galvanically isolated, 9-pin SUB-D plug, UNC)

Display	
<b>DISPLAY CONTRAST RATIO</b>	500:1
<b>DISPLAY LIGHTING</b>	LED Dimmable via software
<b>DISPLAY SIZE</b>	344.23 x 193.54 mm 16:9
<b>DISPLAY TYPE</b>	Color display, TFT, anti-glare TFT Anti-glare tempered glass in

	isolated)
<b>NUMBER OF SLOTS</b>	1 (for SD-Card)
<b>PROTOCOL</b>	EtherCAT CAN TCP/IP EtherNet/IP MODBUS

	plastic bezel
<b>LUMINANCE INTENSITY</b>	400 cd/m <sup>2</sup>
<b>NUMBER OF COLORS OF THE DISPLAY</b>	16777216
<b>RESOLUTION</b>	<ul style="list-style-type: none"> <li>1366 x 768 px</li> <li>WXGA</li> </ul>
<b>SCREEN SIZE (DIAGONAL)</b>	15.6 in
<b>TOUCH TECHNOLOGY</b>	Multi-touch touch panel touch sensor Projected Capacitive Touch (PCT) Capacitive multitouch

System	
<b>BACKUP TIME</b>	10 years, typ. (time at zero voltage)
<b>MEMORY</b>	NVRAM: 128kByte Retain SD card, Type: SDSC, SDHC (external memory) Flash: 1 GByte SLC DRAM: 512 MByte RAM
<b>MEMORY CAPACITY</b>	512,000 kByte
<b>OPERATING SYSTEM</b>	Linux
<b>PROCESSOR</b>	ARM Cortex-A9 800 MHz

Design verification	
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	21.6 W
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0 W
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	0 A
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	21.6 W
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Please enquire
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.

<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Meets the product standard's requirements.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources	
<b>BROCHURES</b>	<a href="#">eaton-xv-303-xv313-hmi-plc-brochure-br050003-en-us</a>
<b>CATALOGUES</b>	<a href="#">eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf</a> <a href="#">eaton-hmi-plc-touch-panel-xv-363-flyer-fl048001en-en-us.pdf</a>
<b>DECLARATIONS OF CONFORMITY</b>	<a href="#">DA-DC-00005047.pdf</a> <a href="#">DA-DC-00005053.pdf</a>
<b>INSTALLATION INSTRUCTIONS</b>	<a href="#">eaton-hmi-xv-303-il048022zu.pdf</a>
<b>MANUALS AND USER GUIDES</b>	<a href="#">eaton-systemdescription-with-embedded-linux-mn050017en-us.pdf</a>

	<a href="#">eaton-hmi-xv300-multi-touchdisplay-manual-mn048031en-us.pdf</a>
<b>MCAD MODEL</b>	<a href="#">eaton-xv_303_15_c00_a00_xc-drawing.dwg</a> <a href="#">eaton-cadenas-front_view-xv_303_15_asmtpl_front_1_front.pra</a> <a href="#">eaton-cadenas-side_view-xv_303_15_asmtpl_side_1_side.pra</a> <a href="#">eaton-cadenas-path-panels-xv_300-assemblies-xv_303_15_c00_1c_asmtpl.prj</a> <a href="#">eaton-xv_303_15_c00_a00_xc-3d-model.stp</a> <a href="#">eaton-cadenas-top_view-xv_303_15_asmtpl_top_1_top.pra</a>
<b>MULTIMEDIA</b>	<a href="#">System solutions based on EtherCAT</a>
<b>PRODUCT NOTIFICATIONS</b>	<a href="#">eaton-xv303-xv313-product-cybersecurity-guideline-mz048009-en-us.pdf</a> <a href="#">eaton-xv303-xv313-end-user-license-agreement-mz048008-en-us.pdf</a>

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

