


## LS 4,6-360 B. Strips, rustfritt stål 4,6x360



Syrefast, rustfritt stål type AISI 316 (ekstra korrosjons-motstandig, ikke magnetisk).  
Glatt stålstrips uten skarpe kanter med selvåsende "kuleås".

Halogenfri: Ja  
Temperaturområde: -80 til +538°C.  
Maks trekkraft: 440 N  
Uv-bestandig: Nei  
Med coating: Nei  
Godkjenninger: Det Norske Veritas, UL og LloydsRegister

### Produktattributter:

|                      |                                 |                                                                                       |  |
|----------------------|---------------------------------|---------------------------------------------------------------------------------------|--|
| Abiko nr.            | LS 4,6-360 B                    |                                                                                       |  |
| Elnummer             | 1343402                         |                                                                                       |  |
| GTIN                 | 7070920002463                   |  |  |
| Farge på strips      | Stål                            |                                                                                       |  |
| Toleranser           | Maks bunt diameter 100mm, 46 kg |                                                                                       |  |
| Ytermål, bredde (B)  | 4,6                             |                                                                                       |  |
| Lengde (L)           | 360                             |                                                                                       |  |
| Maks. bunting        | 100                             |                                                                                       |  |
| Salgsenhet           | STK                             |                                                                                       |  |
| Ant. i pakke         | 100                             |                                                                                       |  |
| Vekt. forpakning (g) | 417                             |    |  |

