



Nexans Ref.: 10590297

Country Ref.: 1050732

EAN 13: 7045210138658

FIRE PERFORMANCE CLASS



Dca-s2,d2,a1

3 or 4 H07Z1-R building wires in one package

STANDARDS

Product EN 50525-2-31

Test IEC 60332-1-2

FIELD OF USE:

For installation inside conduits in buildings.

PN Easy (IX) JetSet consists of 3 or 4 PN-wires with different colour coding, which are spooled together in our EASYpack reel in box. When installing, 3 or 4 wires are pulled simultaneously into conduits, simplifying installation significantly.

PN Easy (IX) JetSet have the same good installation and dismantling properties as the well known PN & PN JetSet.

Nominal diameter denotes values for each conductor.

Colour combinations:

3 cores: Blue - brown - green/yellow

4 cores: Blue - brown - black - green/yellow



Lead free
Yes



Conductor flexibility
Stranded class 2



Rated Voltage Uo/U (Um)
450/750 V



Maximum operating temperature
70 °C



Flame retardant
IEC 60332-1-2



RoHS compliant
Yes

CHARACTERISTICS**Construction characteristics**

Conductor material	Bare annealed copper stranded
Insulation	HFFR
Lead free	Yes
Conductor flexibility	Stranded class 2
Conductor shape	Round, stranded
Sheath colour	Blue, brown, green/yellow
With Green/Yellow core	Yes

Dimensional characteristics

Number of cores	3
Approximate weight	99 kg/km
Conductor diameter	2.0 mm
Nominal outer diameter	3.6 mm
Conductor cross-section	2.5 mm ²
Approximate weight	9.9 kg/100m

Electrical characteristics

Rated Voltage Uo/U (Um)	450/750 V
-------------------------	-----------

Usage characteristics

Packaging	-
Maximum operating temperature	70 °C
Flame retardant	IEC 60332-1-2
Length	100 m
RoHS compliant	Yes