

Datasheet



ENSTO CLAMPO PRO ENSTO

Terminal block Grey, Al/Cu 35-240 mm²

REF. KE64 | 1933071 | EAN. 6418677191916

1-pole, grey, Al/Cu 35-240 mm²

> [Visit e-catalogue](#)

Main description:

1-pole, grey, Al/Cu 35-240 mm²

Description

Ensto Clampo Pro is a comprehensive universal terminal series for Al/Cu conductors of 2.5 – 240 mm².

Technical characteristics

Connectable conductor cross section fine-strand without cable end sleeve (Min-Max)	15 - 185 mm ²
Connectable conductor cross section fine-strand with cable end sleeve (Min-Max)	35 - 185 mm ²
Connectable conductor cross section multi-wired (Min-Max)	35 - 240 mm ²
Rated current In	380 A
Rated voltage	800 V
Type of electrical connection 1	Screw connection
Type of electrical connection 2	Screw connection
Number of levels	1
Number of clamp positions per level	2

Mounting method	Direct mounting
Material insulation body	Thermoplastic
Operating temperature (Min-Max)	-5 - 80 °C
Width	37.5 mm
Height	67 mm
Depth	130 mm
Explosion-tested version 'Ex e'	No
Colour	Grey
Inflammability class of insulation material according to UL 94	V2

Documentation

Technical documentation

 IG_Clampo Pro.pdf | PDF (0.51Mo)

CAD & Design specs / BIM

 DD_KE64.pdf | PDF (0.16Mo)

 2D_KE64.dwg | DWG (0.24Mo)



2D_KE64_2.dxf | DXF (0.81Mo)



3D_KE64_PK2_V1.stp | IFC (4.51Mo)

Agreements & certificates



CE_KE64_2024_FI.pdf | PDF (0.05Mo)



CE_KE64_2024_EN.pdf | PDF (0.05Mo)



LGRP-01862-V01.01-EN.pdf | PDF (0.8Mo)