

# Datasheet



ENSTO CLAMPO PRO ENSTO

Tapping connector Grey, Al/Cu 35-240 mm<sup>2</sup>

REF. KE69 | 1933083 | EAN. 6418677192036

Tapping block, grey, Al/Cu 35-240 mm<sup>2</sup>

> [Visit e-catalogue](#)

## Main description:

Tapping block, grey, Al/Cu 35-240 mm<sup>2</sup>

## Description

Ensto Clampo Pro is a comprehensive universal terminal series for Al/Cu conductors of 2.5 – 240 mm<sup>2</sup>.

## Technical characteristics

|                                                                                    |                          |
|------------------------------------------------------------------------------------|--------------------------|
| Connectable conductor cross section fine-strand without cable end sleeve (Min-Max) | 15 - 185 mm <sup>2</sup> |
| Connectable conductor cross section fine-strand with cable end sleeve (Min-Max)    | 35 - 185 mm <sup>2</sup> |
| Connectable conductor cross section multi-wired (Min-Max)                          | 35 - 240 mm <sup>2</sup> |
| Rated current In                                                                   | 380 A                    |
| Rated voltage                                                                      | 800 V                    |
| Type of electrical connection 1                                                    | Screw connection         |
| Type of electrical connection 2                                                    | Screw connection         |
| Number of levels                                                                   | 1                        |
| Number of clamp positions per level                                                | 4                        |

|                                                                |                 |
|----------------------------------------------------------------|-----------------|
| Mounting method                                                | Direct mounting |
| Material insulation body                                       | Thermoplastic   |
| Operating temperature (Min-Max)                                | -5 - 80 °C      |
| Width                                                          | 64 mm           |
| Height                                                         | 67 mm           |
| Depth                                                          | 130 mm          |
| Explosion-tested version 'Ex e'                                | No              |
| Colour                                                         | Grey            |
| Inflammability class of insulation material according to UL 94 | V2              |

## Documentation

### Technical documentation

 [IG\\_Clampo Pro.pdf](#) | PDF (0.51Mo)

### CAD & Design specs / BIM

 [DD\\_KE269.pdf](#) | PDF (0.19Mo)

 [2D\\_KE269.dwg](#) | DWG (0.27Mo)



3D\_KE69\_PK2\_V1.stp | IFC (6.79Mo)



2D\_KE269\_2.dxf | DXF (0.99Mo)

Agreements & certificates



CE\_KE69\_2024\_EN.pdf | PDF (0.05Mo)



CE\_KE69\_2024\_FI.pdf | PDF (0.05Mo)



LGRP-02011-V01.01-EN.pdf | PDF (0.78Mo)