


Item no. 222-413

CLASSIC Splicing Connector; for all conductor types; max. 4 mm²; 3-conductor; with levers; gray housing; Surrounding air temperature: max 40°C; 2,50 mm²; gray



Color: ●

Stock item

List price per piece* On request
Price and availability after [Login](#)
Your price per piece* On request

PU (SPU): 500 (50) Piece

- 500 +

[Add to shopping cart](#)[Data sheet as PDF](#)[Compare](#)[Bookmark](#)[Configure](#)

Safety information 1:
in grounded power lines

Product details

Details ^

■ Electrical data

■ Ratings per IEC/EN 60664-1

Ratings per	EN 60664
Nominal voltage (II/2)	400 V
Rated surge voltage (II/2)	4 kV
Rated current	32 A
Legend (ratings)	(II / 2) □ Overvoltage category II / Pollution degree 2

■ Connection data

Connection technology	CAGE CLAMP®
-----------------------	-------------

[Global \(EN\)](#)

We will be happy to help!

[+49 \(571\) 887-0](#)

Connectors conductor materials

Lever
Copper

Solid conductor

0,08 ... 2,5 mm² / 28 ... 12 AWG[Contact](#)[Site Notice](#)[Privacy Policy](#)[GTC](#)[Legal Information](#)

© 2020 WAGO



Stranded conductor	0,08 ... 2,5 mm² / 28 ... 12 AWG
■ Geometrical Data	
Width	17 mm / 0.669 inch
Height	14,5 mm / 0.571 inch
Depth	20,5 mm / 0.807 inch
■ Material Data	
Color	gray
Flammability class per UL94	V0
Fire load	0.088 MJ
Color of actuator	orange
Weight	4.3 g
■ Environmental Requirements	
Surrounding air temperature (operation)	40 ... 40 °C
Continuous operating temperature	85 ... 85 °C
■ Commercial data	
Product Group	7 (Push Wire Conn.)
Packaging type	BOX
Country of origin	DE
GTIN	4017332955676
Customs tariff number	85369010000

Approvals / Certificates

Country specific Approvals ^

Logo	Approval	Additional Approval Text	Certificate name	Language	Download
	ENEC 15 UL International Demko A/S	EN 60998	ENEC-01360	Language English ^	

Ship Approvals ^

UL-Approvals ^

Downloads

Documentation ^

■ Additional Information

Language
English ▼

Technical
explanations
3 Apr 2019



CAD/CAE-Data ▼

Compatible products

Mounting adapter ^

ITEM NO.: 222-500
Mounting carrier; 222 Series; for DIN-35 rail mounting/screw mounting; orange



^ Show fewer Show more ▼

Handling Instructions

