


Bergen Cabling DNV GL godkjent LAN S/FTP Cat.7 kabel



Bruksområde

LAN sprednettskabel. Denne kabelen er en DNV GL godkjent Cat7 S/FTP kabel laget for bruk på installasjoner i et sprednett med fokus på brann og røyksikkerhet. Kabelen er testet for transmisjon opp til 900 MHz, og vil gi meget god margin på applikasjoner som 10 Gigabit Ethernet med en båndbredde på opp til 500 MHz og andre som er dekket av standarden. Den er halogenfri og har svak røykutvikling ved brann. Ytterkappen vil også tåle industrielle installasjoner hvor oljesøl kan forekomme.

Standarder

EN 50173-1; EN 50288-4-1
ISO/IEC 11801; IEC 61156-5
Det Norske Veritas (DNV) spesifisering No. 262.1-010028

Brannklasse

LSHF-FR(SHF1) : IEC 60754-2; IEC 61034, IEC 60332-3-24

Konstruksjon

Conductor	Solid copper wire, \varnothing 0.56 mm (AWG 23)
Insulation	foamskin PE, \varnothing 1.4 mm
Twisting	2 cores to the pair
Pair screen	Al-laminated plastic foil
Cable lay up	4 pairs (PiMF) to the core
Screen	copper braid, tinned
Sheath	Oil resistant, Fire retardant and halogen free LSHF-FR (SHF1).

Kjemisk klasse

Mineral oils IRM 902 (IEC60811-2-1) : 7 days/23°C
4 hours/70°C
Diesel - IRM 903 (IEC60811-2-1) : 7 days/23°C
4 hours/70°C

Mekaniske Egenskaper

Bending radius	Without load	8 x D
	With load	4 x D
Temperature range	During operation	-40°C to + 85°C
	During installation	-15°C to + 50°C
Fire load	4 pair	670 MJ/km
Maximum tensile load	During operation	No load
	During installation	200 N

Elektriske egenskaper

ved 20°C± 5°C

Loop resistance		≤ 150 Ω/km
Resistance unbalance		≤ 2%
Insulation resistance	(500 V)	≥ 5000 MΩ*km
Mutual capacitance	at 800 Hz	Nom. 43 nF/km
Capacitance unbalance	(pair/ground)	≤ 1500 pF/km
Characteristic impedance	(1-100 MHz)	(100 ± 5) Ω
	(100 - 250) MHz	(100 ± 10) Ω
	(250 - 600) MHz	(100 ± 15) Ω
Nominal velocity of propagation		ca. 79 %
Propagation delay		≤ 570 ns/100m
Delay skew		≤ 9 ns/100m
Test voltage	(DC, 1 min) core/core and core/screen	1000 V
Transfer impedance(Grade 1)	at 1 MHz	≤ 10 mΩ/m
	at 10 MHz	≤ 10 mΩ/m
	at 30 MHz	≤ 10 mΩ/m
	at 100MHz	≤ 20 mΩ/m
Coupling attenuation		≥ 85 dB

Tekniske Data

Description	Variant	Colour	Outer diameter (D) mm	Delivery form	Weight kg/km	BC No.
Maritime LAN Cat.7 S/FTP 4x2/0.56	LSHF-FR(SHF1)	Grey RAL7035	7,8	Reel 500m EuroPallet 6000m	67	10-001

Sertifisering

DNV GL approved for Maritime and Offshore. Certificate NO: TAE0000009

Elektriske data (nominell)

iht. Cat.7 (ved 20 °C)

F (MHZ)	Attenuation (dB/100m)	NEXT (dB)	PS-NEXT (dB)	ACR (dB/100m)	PS-ACR (dB/100m)	ELFEXT (dB/100m)	PS-ELFEXT (dB/100m)	Return loss (dB)
1,0	1,8	100	97	98	95	105	105	-
4,0	3,4	100	97	97	94	105	102	27
10,0	5,4	100	97	95	92	97	94	30
16,0	6,8	100	97	93	90	93	90	30
20,0	7,7	100	97	92	89	91	88	30
31,2	9,6	100	97	90	87	87	84	30
62,5	13,7	100	97	86	83	81	78	30
100,0	17,4	100	97	83	80	77	74	30
125,0	19,5	95	92	75	72	75	72	26
155,5	21,9	94	91	72	69	73	70	26
175,0	23,3	93	90	70	67	72	69	25
200,0	25,0	92	89	67	64	71	68	25
250,0	28,1	90	87	62	59	69	66	24
300,0	30,9	89	86	58	55	67	64	24
450,0	38,3	87	84	48	45	64	61	23
600,0	44,8	85	82	40	37	61	58	22
750,0	52,0	83	80	31	28	59	56	21
900,0	59,4	82	79	23	20	58	55	20

Gassing/trevirke

No fumigation needed. The cable is delivered on environmental plastic reels.

Bestillingsinformasjon

El Nr.	Part Name
1000801	Cat7 S/FTP DNV GL LAN