

- Worldwide English

[Overview](#) [Specifications](#) [Resources](#)

EL-Nummer (Norway)

1600287

Fuse, fuse-link, low voltage, 16 A, AC400 V, D01, gL/gG, IEC, time-delay, E14, for domestic and general industrial applications, IEC 60269-3, VDE 0636

- 
- 
- 
- 
-
-
- Delivery program
- Technical data

Product range

Fuse
 Basic function
 Fuse-link
 Field of application
 low voltage
 Rated current [I]
 16 A
 Rated voltage
 AC 400 V
 Construction size
 D01
 Utilization category
 gL/gG
 Breaking Capacity
 50 kA
 usable for size/applications
 E14
 for domestic and general industrial applications
 Release characteristic [class]
 time-delay
 Standard/Approval
 IEC
 Shape
 bottle
 Standards/Regulations
 IEC 60269-3
 VDE 0636

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / D0-system fuse link (EC001642)
 Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems /
 Neozed fuse link (ecl@ss10.0.1-27-14-21-19 [ACN353011])
 Construction size
 D01
 Rated current
 16 A
 Rated voltage
 400 V
 Colour code
 Grey
 Utilization category
 gL/gG (cable protection/equipment protection)

Product photo



[16nz01_b](#)
 Photo



[16nz01_c](#)
 Photo



[16nz01_pkg](#)
 Photo



[16nz01_r](#)

Photo



[nz01_c](#)

Photo



[nz01_l](#)

Photo



[nz01_r](#)

Photo

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

