



JUNCTION BOX

Abox GT 060-6²



Abox GT 060-6²

Junction box

CUSTOMIZABLE

110 x 110 x 67 mm
Article number: 49240601

Junction box - Industrial Quality - acc. DIN EN 60529 and VDE 0278-623, weather-resistant and shockproof, Ui=690V, with double-membrane seals M25, seal range 9 - 16 mm, with cast resin bag 600 ml (markingfree), funnel, ventilation seals and disposable gloves, attention: note the expiration date of the cast-resin bag

grey, with high-set screw terminal, 5-pole - 6 mm² (4 x 2.5² / 4 x 4² / 3 x 6²)



Technical data

Measures

Width:	110 mm
Length:	110 mm
Height:	67 mm

Material

Base:	polycarbonate, glass fiber-reinforced
Cover:	polycarbonate, glass fiber-reinforced

Other attributes

Entries:	9
Rated cross section:	6 mm ²
Tackable:	No

Accessory

KVR M25-MGM

KVR M20-GDB/MGM

KVR M20-MGM

VST M25-or

VST M20-or

AST M25-or

AST M20-or

DMS M25

AST M25

AST M20

KVR M25

KVR M20-GDB

KVR M20

GMU PA M25

GMU PA M20

ADR M25



JUNCTION BOX

Abox GT 060-6²

Rated insulation voltage AC:	690 V	ADR M20
Explosion safety:	none	WST M25
Fire protection:	none	WST M20
sealable:	No	WNI M25
Equipment:	Terminal	WNI M20
Heavy metals-free:	Yes	VST M25
PVC-free:	Yes	VST M20
Silicone-free:	Yes	VSS PA M25
Ingress protection:	IP68 - acc. EN 60529 / DIN VDE 0470-1	VSS PA M20
Weatherproof:	Yes	SNI M25
		SNI M20
		BST M20
		KS M25
		KS M20