

SPECIFICATION
S015888**2.6.2015 VR**
1(3)**HALOGEN FREE POWER AND CONTROL CABLE FOR MARINE APPLICATIONS****TEMAR PHFX-U 0,6/1 kV class 5 and LM-HF 0,6/1 kV class 5**

APPLICATION	Power and control cable for fixed installations. Designed to fulfill requirements for cabling on ships.
STANDARDS	
Construction	IEC 60092-353 and IEC 60092-350
Materials	IEC 60228 (conductor), IEC 60092-360 (insulation and sheath)
Flame retardance	IEC 60332-3-22 (cat A) and IEC 60332-1-2
Halogen free properties	IEC 60754-1 and -2
Low smoke emission	IEC 61034-1 and -2
Tests	IEC 60092-353
Choice and installation	IEC 60092-352
CHARACTERISTICS	
Rated voltage	0,6/1 (1,2) kV
Conductor temperature	Maximum +90 °C
Ambient temperature	Minimum -15 °C (Installation)
DESIGN	
Conductor	Round stranded flexible plain copper conductor - max dc-resistance at +20 °C i.a.w. IEC 60228 class 5 (see tables 1-2)
Insulation	Extruded halogen free XLPE, i.a.w. IEC 60092-360 - nominal thickness i.a.w. IEC 60092-353 (see tables 1-2) - possible separator tape under the insulation
Laying up	In multicore cables insulated conductors are laid up together - wrapping with suitable tape
Inner covering	In multicore cables possible extruded halogen free inner covering
Sheath	Extruded black halogen free polyolefine, SHF1 i.a.w. IEC 60092-360 - nominal thickness i.a.w. IEC 60092-353 (see tables 1-2)

SPECIFICATION

S015888

2.6.2015 VR
2(3)

IDENTIFICATION

Cable Marking examples

PRYSMIAN (FI10) TEMAR PHFX-U 3x70 F 0,6/1 kV LM-HF
PRYSMIAN (FI10) TEMAR PHFX-U 1x240 F 0,6/1 kV LM-HF
+ IEC60092-353 +meter marking +manufacturing time

Core colours (cable without earth core)

Type	N	Live		
1X			(Black)	
3X		Brown	Black	Grey
4X	Blue	Brown	Black	Grey

Core colours (cable with earth core)

Type	PE	N	Live		
3G	G Y	Blue	Brown		
4G	G Y		Brown	Black	Grey
5G	G Y	Blue	Brown	Black	Grey

TECHNICAL DATA

Table 1. Single core power cable dimensions TEMAR PHFX-U and LM-HF class 5

Size (nxmm ²)	Conductor		Insulation thickness nominal (mm)	Sheath thickness nominal (mm)	Cable	
	resistance max. (Ω/km)	diameter approx. (mm)			diameter approx. (mm)	weight approx. (kg/km)
1x25 F	0,780	6,5	0,9	1,1	11,5	300
1x35 F	0,554	7,6	0,9	1,1	12,5	400
1x50 F	0,386	9,2	1,0	1,2	14,5	550
1x70 F	0,272	11,0	1,1	1,3	16,5	760
1x95 F	0,206	13,5	1,1	1,3	19,0	980
1x120 F	0,161	15,0	1,2	1,4	21,0	1250
1x150 F	0,129	17,5	1,4	1,5	24,0	1550
1x185 F	0,106	18,5	1,6	1,5	26,0	1850
1x240 F	0,0801	21,0	1,7	1,6	29,0	2400
1x300 F	0,0641	24,0	1,8	1,7	33,0	3000

SPECIFICATION
S015888
2.6.2015 VR
3(3)
Table 2. Multicore power cable dimensions TEMAR PHFX-U and LM-HF class 5

Size (nxmm ²)	Conductor		Insulation thickness nominal (mm)	Sheath thickness nominal (mm)	Cable	
	resistance max. (Ω/km)	diameter approx. (mm)			diameter approx. (mm)	weight approx. (kg/km)
3x35 F	0,554	7,6	0,9	1,6	28,0	1550
3x50 F	0,386	9,2	1,0	1,7	32,0	2150
3x70 F	0,272	11,0	1,1	1,9	37,0	3000
3x95 F	0,206	13,5	1,1	2,0	42,0	3900
3x120 F	0,161	15,0	1,2	2,2	46,0	4900
3x150 F	0,129	17,5	1,4	2,3	53,0	6100
3x185 F	0,106	18,5	1,6	2,5	57,0	7300
4x35 F	0,554	7,6	0,9	1,7	31,0	2000
4x50 F	0,386	9,2	1,0	1,8	35,0	2700
4x70 F	0,272	11,0	1,1	2,0	41,0	3800
4x95 F	0,206	13,5	1,1	2,2	47,0	4900
4x120 F	0,161	15,0	1,2	2,3	52,0	6200
4x150 F	0,129	17,5	1,4	2,5	58,0	7700
4x185 F	0,106	18,5	1,6	2,7	62,0	9100
5G35 F	0,554	7,6	0,9	1,8	33,0	2400
5G50 F	0,386	9,2	1,0	2,0	39,0	3400
5G70 F	0,272	11,0	1,1	2,1	45,0	4700
5G95 F	0,206	13,5	1,1	2,3	52,0	6100

Ordering information:

Part number	Description	GTIN no.	EL nummer
20132351	TEMAR PHFX-U 1x25 F 1kV	6410006241811	10 950 20
20132352	TEMAR PHFX-U 1x35 F 1kV	6410006241972	10 950 21
20131547	TEMAR PHFX-U 1x50 F 1kV	6410006241910	10 950 22
20131548	TEMAR PHFX-U 1x70 F 1kV	6410006241828	10 950 23
20131549	TEMAR PHFX-U 1x95 F 1kV	6410006241927	10 950 24
20132353	TEMAR PHFX-U 1x120 F 1kV	6410006241835	10 950 25
20132354	TEMAR PHFX-U 1x150 F 1kV	6410006241989	10 950 26
20132355	TEMAR PHFX-U 1x185 F 1kV	6410006241842	10 950 27
20132356	TEMAR PHFX-U 1x240 F 1kV	6410006241996	10 950 28
20132357	TEMAR PHFX-U 1x300 F 1kV	6410006242009	10 950 29
20132360	TEMAR PHFX-U 3x25 F 1kV	6410006242016	10 950 30
20132361	TEMAR PHFX-U 3x35 F 1kV	6410006242023	10 950 31
20131952	TEMAR PHFX-U 3x50 F 1kV	6410006241934	10 950 32
20132362	TEMAR PHFX-U 3x70 F 1kV	6410006241859	10 950 33
20131953	TEMAR PHFX-U 3x95 F 1kV	6410006241866	10 950 34
20131954	TEMAR PHFX-U 3x120 F 1kV	6410006241941	10 950 35
20132363	TEMAR PHFX-U 3x150 F 1kV	6410006241873	10 950 36
20132364	TEMAR PHFX-U 3x185 F 1kV	6410006242030	10 950 37
20180834	TEMAR PHFX-U 4x35 F 1kV	6410006242245	10 950 38
20180835	TEMAR PHFX-U 4x50 F 1kV	6410006242269	10 950 39
20180836	TEMAR PHFX-U 4x70 F 1kV	6410006242283	10 950 40
	TEMAR PHFX-U 4x95 F 1kV		10 950 41
	TEMAR PHFX-U 4x120 F 1kV		10 950 42
20180820	TEMAR PHFX-U 4x150 F 1kV	6410006242320	10 950 43
20180821	TEMAR PHFX-U 4x185 F 1kV	6410006242344	10 950 44
20180822	TEMAR PHFX-U 5x35 F 1kV	6410006242689	10 950 45
20180838	TEMAR PHFX-U 5x50 F 1kV	6410006242368	10 950 46
20180823	TEMAR PHFX-U 5x70 F 1kV	6410006242375	10 950 47
20180824	TEMAR PHFX-U 5x95 F 1kV	6410006242382	10 950 48