

H6-3-P5-B46-S3-3-P

Technical information for this product:

AC inngangsspenning: 90-305VAC

AC Kontakt: 5 pinner Bulgin PX0911

Total belastning ved 230VAC: 10A

DC LED lys utganger: 4

DC Max pr. LED lys: 2.4A

DC spenning pr. LED lys: 180-240VDC

DC Kontakt: PL-CMB-600

AC Utganger: 3

AC Output Connector: 4 pin Amphenol Eco-mate

AC Utgang Kontakt: 4 pinner Amphenol ECO-mate

Vekt (uten brakett): 28kg

Ytre kabinettmateriale: 316 Stainless Steel

Ytre kabinett IP grad: IPX5

IP grad styringsskap: IP68

And the original English version if it helps is:

AC Input Voltage: 90-305VAC

AC Connector: 5 pin Bulgin PX0911

Total Load @230VAC: 10A

DC Lighting Outputs: 4

DC Max Current: 2.4A

DC Voltage: 180-240VDC

DC Connector: PL-CMB-600

AC Outputs: 3

AC Output Max Load: 2A

AC Output Connector: 4 pin Amphenol Eco-mate

Weight (without bracket): 28kg

Outer Cabinet Material: 316 Stainless Steel

Outer Cabinet IP Rating: IPX5

Electrical System IP Rating: IP68

