



Data Sheet 1223831

Product: Flexi Abox 2M, 13 mm, 4 stubs+beam fire
EI-number: 1223831
Mat.no: EKO07421
EAN:
Packing:
Color: Red



Product description:

Flexi+ double fireprotectionbox with 4 tubeintroductions, approved for use in firewalls EI30, EI60 or EI90. The cutout for the box must not exceed 74mm, and must be done with a cutter. The firebox has to be centered in the hole. See document kombinasjoner for approved combinations.


Flexi+ flushmounted doublebox with 4 tubeintroductions and beamfixing. Double box is mostly used for 2 module products, or to replace two single boxes for switches or dimmers. Possible to use with two board walls, with extension ring (el.nr: 12 238 13)

Integrated docking to make boxcombinations easy. The box is combinable with a good variety of accessories available. Flexi+ box is delivered with 20mm tubeinserts with 16mm reduction.

Technical specifications:

Flush mounted box.
Diameter: \varnothing :71mm
Fixing screws: C-C 60mm
Halogenfree: Yes
Certified: NEMKO, SEMKO, FIMKO
Glow wire test: 850°C
Degree of protection: IP30
Suitable for plates: 13mm
Cuttersize: 73mm
Fireprotection approval: RISE C9001152
See userguide and approval document for further information.

Size



Wiring diagram

Applicable installations and combinations related to fire class

	1	2	3	4	5	6	7	8
EI 60	✓	✓	✓	✓	✓	✓	✓	✓
EI 90	✓	✓	✓	✓	✓	✓	✓	✓

ELKO AS

E-mail: elko@elko.no
Internet: www.elko.no
Bank: 6219.05.15880
Org.no.: NO 911 382 563 MVA

ELKO Front office
Sandstuveien 68, NO-0680 Oslo
P.O.Box 6598 Etterstad, NO-0607 Oslo
Tel.: +47 67 80 73 00
Fax: +47 67 80 73 01

ELKO Plant
Sporpind Industriområde, NO-3340 Åmot
Tel.: +47 32 78 91 00
Fax: +47 32 78 91 01